

Certifications

- ISO9001; ISO14001, HSMS18001; CE
- Certificate from Ministry of Public Security Safety & Police Electronic Products Quality Inspection Center
- In accordance with: EN60950, WN50081-1, EN50082-1
- Electric safety: EN60950
- Anti-interference standard: EN50082-1

Features

- Stable performance, 6-12-18 zones options
- · Extremely high sensitivity to find even tiny threats
- IP-55 weather proof design
- Two LED lights, sound and light alarm
- IP-55 weatherproof design, supporting outdoor work.
- Operation: Remote control only.
- Two LED light bars on both door panels: Gives alarm corresponding to the height or human body.
- 6 Pinpoint zones: Can precisely identify multiple target locations from head to toe, can update 12 to 18 zones.
- Advanced broadband detection technology: can detect ferrous and non-ferrous articles.
- Sensitivity adjustable from Level 0 to 99 High: Can detect up to a clip. Low: Detects big metal articles such as: knives, guns, copper, aluminum, zinc

(more than 150g), bypassing metal in belt, buttons and shoes.

- Shock proof to avoid false alarms.
- Sound and light alarm.
- Intelligent traffic & alarm counters that calculate traffic flow & resultant alarms.

2MWT-300A

Walk-through Metal Detector

- Tamper-Proof: Operating system is password protected.
- Adjustable operating frequencies: Helps eliminate the potential interference from X-ray units, radios and other electrical items.
- Mix distances between two Walk-throughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity.
- Harmless to pregnant women and heart pacemakers.
- Connect with computer, camera, turnstile, etc... (optional)

Specifications

	1
Zone Options	6-12-18 zones options
Shock Proof	Yes
LED Lights	2
Operation	Remote control only
Pinpoint Zones	6 Pinpoint zones: Can precisely identify multiple target locations from head to toe, can update 12 to 18 zones
Tracking	Intelligent traffic & alarm counters that calculate traffic flow & resultant alarms
Advanced Broadband Detection	Can detect ferrous and non-ferrous articles
Alarm	Audible and Visual Alerts
Adjustable Sensitivity	From Level 0 to 99
Tamper Proof	Password Protected
Operating Frequencies	Adjustable
Distance	Mix distances between two Walk-throughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
Safety	Harmless to pregnant women and heart pacemakers
Electrical Current	AC215V~230V; 50/60Hz
Power	35W
IP Rating	IP-55
Work Environment	-20°C~+45°C
Gross Weight	95 kg
Outer Frame	2220(h) x 820(w) x 522(d) (mm)
Inner Frame	2000(h) x 700(w) x 522(d) (mm)

F© (ERoHS