

## 2MWT-IIIC Walk-through Metal Detector



## Certifications

- IS09001; IS014001; HSMS18001; CE
- · Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center
- In accordance with: EN60950, WN50081-1, EN50082-1
- Electric safety: EN60950
- Anti-interference standard: EN50082-1

## Features

- Stable performance, 6-12-18 zones options
- · Extremely high sensitivity to find even tiny threats
- · Operation: keyboard
- Two LED lights, sound and light alarm
- Two LED light bars on both door panels: Gives alarm corresponding to the height or human body.
- .Advanced broadband detection technology: Can detect ferrous and non-ferrous articles.
- Sensitivity adjustable from Level 0 to 300 High: Can detect up to a clip. Low: Can detect big metal articles such as: knives, guns, copper, aluminum, zinc (more than 150g), bypasses metal in belts, buttons and shoes.
- Shock proof to avoid false alarms.
- · Sound and light alarm.
- · Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.

- Adjustable operating frequencies: Helps eliminate the potential interference from X-ray units, radios and other electrical items.
- Mix distances between two Walk-throughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity.
- Harmless to pregnant women and heart pacemakers.
- Remote control (optional).
- Connect with computer, camera, turnstile, etc... (optional)

## Specifications

Zone Options	6-12-18 zones options
Shock Proof	Yes
LED Lights	2
Operation	Keyboardy
Pinpoint Zones	6 Pinpoint zones: Can precisely identify multiple target locations from head to toe, can update 12 to 18 zones
Tracking	Intelligent traffic & alarm counters that calculate traffic flow & resultant alarms
Advanced Broadband Detection	Can detect ferrous and non-ferrous articles
Alarm	Audible and Visual Alerts
Adjustable Sensitivity	From Level 0 to 300
Tamper Proof	Password Protected
<b>Operating Frequencies</b>	Adjustable
Distance	Mix distances between two Walk-throughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
Safety	Harmless to pregnant women and heart pacemakers
Electrical Current	AC215V~230V; 50/60Hz
Power	35W
Work Environment	-20°C~+45°C
Gross Weight	95 kg
Outer Frame	2220(h) x 820(w) x 522(d) (mm)
Inner Frame	2000(h) x 700(w) x 522(d) (mm)



FC ( E RoHS