



Model :

2MEXD-1312-L: 42cm IP66 explosion proof camera housing made with 316L stainless steel, included wiper and sun shield.

Available models :

Model	Material
2MEXD-1312	AISI 304 stainless steel
2MEXD-1312-L	AISI 316L stainless steel

Features :

- IP-66, NEMA-4X Enclosure rating
- Operating temperature range from -25°C to 60°C (-13°F to 140°F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Wiper and sun shield included

Specifications

Type	Back opening
Atmospheric Pressure	80 kPa 106 kPa
Operating Ambient Temp	-25°C to 60°C (-13°F to 140°F)
Relative Humidity	5 % to 95 % nocondensing
Protection rating	<ul style="list-style-type: none"> • Ex d IIC T6 Gb Explosin-proof marking • IP66, NEMA-4X enclosure rating
Input Power	85 V AC to 265 AC, 24 V AC
Dimensions (W x H x L)	(195 x 194 x 420 mm) (7.68 x 7.64 x 16.54 In)
Internal Usable Size (Ø x L)	(80 x 210 mm) (3.15 x 8.27 In)
Window Thickness	12 mm (0.47 in)
Window Viewing Area (Ø)	69.5 mm (2.74 in)
Weight	11 Kg (24.25 lb) 12.8 Kg (28.22 in) (wall mount bracket included)
Material	<ul style="list-style-type: none"> • AISI 304 stainless steel 2MEXH-3616WS • AISI 316L stainless steel 2MEXH-3616WS-L
Heater Control	On at 15°C ± 3°C (59°F ± 5°F) Off at 25°C ± 3°C (77°F ± 5°F) (Optional)

*Design and specifications are subject to change without prior notice.