



Features

- Small size explosion-proof camera housing
- IP68, NEMA-6P enclosure rating
- Operating temperature range from -25°C to 60°C (-13°F to 140°F)
- Ex d IIB T6 Gb explosion-proof marking
- AISI 304 or 316L stainless steel construction available


Available Models

MODEL	MATERIAL
2MEXH-3616	AISI 304 Stainless Steel
2MEXH-3616-L	AISI 316L Stainless Steel

Accessories



2MEXPTB-3623 / 2MEXPTB-3623-L
Heavy Explosion-Proof Pan and Tilt Unit



2MEXB-2915 / 2MEXB-2915-L
Explosion-Proof Wall Housing Bracket

Specifications

CERTIFICATION	
Explosion-Proof Marking	Ex d IIB T6 Gb
Enclosure Rating	IP68, NEMA-6P
ELECTRICAL	
Input Power	AC 220 V, 50 Hz (optional)
ENVIRONMENTAL	
Atmospheric Pressure	80–106 KPa
Operating Temperature	-25°C to +60°C (-13°F to +140°F)
Operating Humidity	5–95% RH (non-condensing)
GENERAL	
Material	AISI 304 Stainless Steel, AISI 316L Stainless Steel (optional)
Dimensions (L × W × H)	365.5 × 163 × 169.5 mm (14.39" × 6.42" × 6.67")
Internal Usable Dimensions (L × W × H)	260 × 80 × 80 mm (10.24" × 3.15" × 3.15")
Window Viewing Area (Ø)	79 mm (3.11")
Weight	5.5 kg (12.13 lb)
Heater Control	On at 1°C ± 3°C (34°F ± 5°F) (optional)

Dimensions

