

2MFIP-4MIR10U-P 4MP Fisheye Fixed Lens IP Camera



Key Features

Optics

- Ultra wide angle lens, 180°panoramic image
- Smart IR, Up to 10 m (33ft) IR distance
- 3D DNR (Digital Noise Reduction)

Compression

- H.265, H.264, MJPEG
- Single stream (1 panoramic view)

Network

- ONVIF Conformance

Structure


- Support PoE power supply
- Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- Wide voltage range of $\pm 25\%$
- IK10
- IP66

Specifications

	2MFIP-4MIR10U-P
Camera	
Image sensor	1/3", 4 megapixel, progressive scan, CMOS
Aperture	F1.6
Shutter	Auto/Manual shutter time : 1/6 s ~1/100000 s
Minimum Illumination	Color: 0.02 Lux (F1.6, AGC ON) 0 Lux with IR
S/N Ratio	>55dB
Day / Night	IR-cut filter for day & night function
WDR	120 dB
Video	
Max. Resolution	2592×1520
Video Compression	H.265, H.264, MJPEG
Frame Rate	4MP (2560×1440): Max.25 fps
ROI(Region of Interest)	Supported
Maximum Streams	Single stream (1 panoramic view)
Evaluative Metering	Supported
OSD	Up to 8 OSD
Privacy Mask	Supported
Storage	
Edge Storage	Micro SD, up to 128GB
Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x
Compatible Integration	ONVIF, API
Interface	
Network	10M/100M Base-TX Auto-adaptive Ethernet
Reset	1 Reset Button
General	
Power	DC12V±25%,PoE(IEEE 802.3af)
	Power consumption: Max. 11 W
Dimensions (Ø x H)	Φ125x 43.7 mm (Φ4.9" x 1.7")

Weight	0.39kg(0.86lb)
Working Environment	-40°C ~60°C (-40°F ~ 140°F), Humidity≤95% RH
Vandal Resistant	IK10
Ingress Protection	IP66

Dimensions



*Product specifications and availability are subject to change without notice.