



## Specifications

CAMERA	
<b>Image sensor</b>	1/3", 4 megapixel, progressive scan, CMOS
<b>Aperture</b>	F1.6
<b>Shutter</b>	Auto/Manual shutter time:1/6 s ~1/100000 s
<b>Minimum Illumination</b>	Color: 0.02 Lux (F1.6, AGC ON) 0 Lux with IR
<b>S/N Ratio</b>	>55dB
<b>Day / Night</b>	IR-cut filter for day & night function
<b>WDR</b>	120 dB
VIDEO	
<b>Max. Resolution</b>	2592×1520
<b>Video Compression</b>	H.265, H.264, MJPEG
<b>Frame Rate</b>	4MP (2560×1440): Max.25 fps
<b>ROI(Region of Interest)</b>	Supported
<b>Maximum Streams</b>	Single stream (1 panoramic view)
<b>Evaluative Metering</b>	Supported
<b>OSD</b>	Up to 8 OSD
<b>Privacy Mask</b>	Supported
STORAGE	
<b>Edge Storage</b>	Micro SD, up to 128GB
NETWORK	
<b>Protocols</b>	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x
<b>Compatible Integration</b>	ONVIF, API
INTERFACE	
<b>Network</b>	10M/100M Base-TX Auto-adaptive Ethernet
<b>Reset</b>	1 Reset Button
GENERAL	
<b>Power</b>	DC12V±25%,PoE(IEEE 802.3af) Power consumption: Max. 11 W
<b>Dimensions (Ø x H)</b>	125x 43.7 mm (4.9" x 1.7")
<b>Weight</b>	0.39kg (0.86lb)
<b>Working Environment</b>	-40°C ~60°C (-40°F ~ 140°F), Humidity≤95% RH

## Features

### Optics:

- Ultra wide angle lens, 180°panoramic image
- Smart IR, Up to 10 m (33ft) IR distance
- 3D DNR (Digital Noise Reduction)

### Compression:

- H.265, H.264, MJPEG
- Single stream (1 panoramic view)

### Network:

- ONVIF Conformance

### Structure:

- Support PoE power supply
- Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- Wide voltage range of ±25%
- IK10
- IP66

# 2MFIP-4MIR10U-P

4MP Fisheye Fixed Lens IP Camera

<b>Vandal Resistant</b>	IK10
<b>Ingress Protection</b>	IP66

## Dimensions

