



Specifications

CAMERA					
Image sensor	1/3", progressive scan, 4.0 megapixel, CMOS				
Lens	1.6mm@ F1.6				
DORI Distance	Lens	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	1.6mm	36	14.4	7.2	3.7
Angle of View	180°				
Shutter	Auto/Manual shutter time: 1~1/100000 s				
Minimum Illumination	Colour: 0.01 Lux (F1.6, AGC ON) 0 Lux with IR				
Day / Night	IR-cut filter for day & night function				
Digital noise reduction	2D/3D DNR				
S/N	>55dB				
IR Range	UP to 10m (33ft)				
Defog	Digital Defog				
WDR	120dB				
VIDEO					
Compression	Ultra265, H.264,MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream : (2560×1440) : Max.25fps; Sub Stream: (1920×1080) : Max.25fps; Third Stream: D1 (720 x 576): Max.25 fps				
BLC	Supported				
OSD	Up to 8 OSDs				
ROI	Up to 8 areas				
Privacy Mask	Up to 8 areas				
Motion Detection	Up to 4 areas				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
AUDIO					
Audio Compression	G.711				
Two-way audio	Supported				
Suppression	Supported				
Sampling Rate	8 KHZ				

Features

Optics:

- Ultra wide angle lens, 180°panoramic image
- Smart IR, Up to 10 m (33ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)

Compression:

- H.265, H.264, MJPEG
- Built-in omni directional microphone
- Triple stream (3 panoramic view)

Network:

- ONVIF Conformance

Structure:

- Support PoE power supply
- Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- Wide voltage range of ±25%
- IK10
- IP66

STORAGE

Edge Storage	Micro SD, up to 128GB
Network Storage	ANR

NETWORK

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API

Mount Type	Support table, wall, and ceiling
-------------------	----------------------------------

Display Mode	Support 9 display modes in total (including display modes of mount types and decoding modes): Original Image, Fisheye + 4PTZ, Panoramic, 360°Panoramic+1PTZ, 180°Panoramic, Fisheye + 3PTZ, Fisheye+4PTZ, 360°Panoramic + 6PTZ, Fisheye + 8PTZ
---------------------	---

INTERFACE

Audio I/O	Audio interface
	Input: impedance 35 kΩ; amplitude 2 V *p-p]
	Output: impedance 600 Ω; amplitude 2 V *p-p]
	3 built-in omnidirectional microphone

Alarm I/O	1 / 1
------------------	-------

Built-in Mic	Supported
---------------------	-----------

Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
---------------------	--

Network	1 RJ45 10M/100M Base-TX Auto-adaptive Ethernet
----------------	--

GENERAL

Power	DC12V ±25%, PoE (IEEE 802.3af)
	Power consumption: Max. 11 W

Dimensions (Ø x H)	125x 43.7 mm (4.9" x 1.7")
---------------------------	----------------------------

Weight	0.39kg(0.86lb)
---------------	----------------

Working Environment	-40°C ~60°C (-40°F ~ 140°F), Humidity :10%~95% RH
----------------------------	---

Ingress Protection	IP66
---------------------------	------

Vandal Resistant	IK10
-------------------------	------

Reset Button	Supported
---------------------	-----------

Dimensions

