



Specifications

CAMERA		
Sensor	1/2.9" progressive scan, 2.0 megapixel, CMOS	
Lens	5.2~ 114.4 mm (22x optical zoom) AF automatic focusing and motorized zoom lens	
Angle of View (H)	54.43° (wide) ~ 3.45° (tele)	
Shutter	Auto/Manual, shutter time: 1/6 s ~ 1/100000 s	
Min. Illumination	Colour: 0.06 lux (F1.5,AGC ON) 0 lux with IR	
Iris	F1.5	
CAMERA FEATURES		
Day/Night	IR-cut filter with auto switch (ICR)	
Digital noise reduction	2D/3D DNR	
S/N	>55 dB	
IR Range	UP to 150m (492ft)	
Defog	Digital Defog	
WDR	DWDR	
VIDEO		
Video Compression	Ultra 265,H.265, H.264, MJPEG	
H.264 code profile	Baseline profile, Main Profile, High Profile	
Frame Rate	Main Stream:2MP (1920×1080): Max. 30 fps; Sub Stream:2MP (1920×1080): Max. 30 fps; Third Stream: D1 (720×576): Max. 30 fps	
HLC	Supported	
BLC	Supported	
EIS	Supported	
OSD	Up to 8 OSDs	
Privacy Mask	Up to 8 areas	
ROI	Up to 8 areas	
Motion Detection	Up to 4 areas	
Behavior Detection	Intrusion, cross line, motion detection	
Exception Detection	N/A	Audio detection
Intelligent Identification	Face detection	
Statistical Analysis	People counting	
General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication

Features

Optics:

- 22X Optical Zoom
- Fifth-generation infrared technology, more than 150m (492ft) IR distance
- IR anti-reflection window to increase the infrared transmittance
- Optical glass window with higher light transmittance
- EIS (Electronic Image Stabilization)

Compression:

- Ultra 265,H.265, H.264, MJPEG
- Triple streams
- Embedded smart algorithm Triple streams
- Customized OSD

Network:

- ONVIF Conformance

Network:

- Intelligent temperature control technology
- More effective heat dissipation system
- 6 KV surge protection designed for network interface
- IP66

AUDIO		
Audio Compression	N/A	G.711
Two-way Audio	N/A	Supported
Suppression	N/A	Supported
Sampling Rate	N/A	8 KHZ
INTELLIGENT FUNCTION		
Edge Storage	Micro SD, up to 128 GB	
Network Storage	ANR	
NETWORK		
Protocol	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP	
Compatible Integration	ONVIF(Profile S, Profile G), API	
INTERFACE		
Audio I/O	N/A	1 Input: impedance 35 k Ω ; amplitude 2 V [p-p]
	N/A	1 Output: impedance 600 Ω ; amplitude 2 V [p-p]
Alarm I/O	N/A	1/ 1
Network	1 RJ45 10M/100M Base-TX Ethernet	1 RJ45 10M/100M Base-TX Ethernet
GENERAL		
Power Supply	DC 12V \pm 10%	DC 12V \pm 10%, PoE (PSE Required)
	Power consumption: 24 W	
Dimensions (Ø x H)	6 inch 215mm x 344mm (8.5" x 13.5")	
Weight	3kg (6.6lb)	
Working Environment	-40°C ~ +65°C (-40°F ~ 149°F), Humidity: 10%~90% RH (non-condensing)	
Ingress Protection	IP66	
Reset Button	Supported	

Dimensions

