

2MTIP-4MIR30ZUA-P

4MP WDR (Motorized) VF Eyeball Network IR Camera



Specifications

CAMERA	
Sensor	1/3", 4megapixel, progressive scan, CMOS
Lens	2.7~12 mm@F1.4
Angle of View (H)	91.0°~27.0°
Zoom/Focus	Motor drive
Shutter	Auto/Manual, shutter time: 1/6 s ~ 1/100000 s
Minimum Illumination	Color: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
WDR	120dB
VIDEO	
Max. Resolution	2592x1520
Video Compression	H.265, H.264, MJPEG
Frame Rate	4MP (2592×1520): Max.20 fps; 4MP (2560×1440): Max.25 fps
Video Streaming	Triple
9:16 Corridor Format	Supported
ROI	Supported
Evaluative Metering	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
Motion Detection	Up to 4 areas
SMART	
Behavior Detection	Intrusion, crossing line, motion detection
Intelligent Identification	Face detection, Defocus, Scene Change
Statistical Analysis	People counting
STORAGE	
Edge Storage	Micro SD, up to 128 GB
NETWORK	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x
Compatible Integration	ONVIF, API
INTERFACE	
Built-in Mic	Supported
Network	10M/100M Base-TX Ethernet

Features

Optics:

- Day/night functionality
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- Smart IR, up to 30 m (98 ft) IR distance
- 3D DNR (Digital Noise Reduction)

Compression:

- Ultra 265, H.265, H.264, MJPEG
- Embedded smart algorithm
- Triple streams
- 9:16 corridor mode

Network:

- ONVIF Conformance

Structure:

- Support PoE power supply
- Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- Wide voltage range of ±25%
- IP67

2MTIP-4MIR30ZUA-P

4MP WDR (Motorized) VF Eyeball Network IR Camera

GENERAL

Power Supply	12 V DC ±25%, PoE (IEEE802.3 af) Power consumption: Max 8.16W
Dimensions (Ø x H)	129 x 110 mm (Ø5.08" x 4.3")
Weight	0.67 kg (1.48lb)
Working Environment	-40°C ~ +60°C (-40°F ~ 140°F), Humidity :10%~95% RH (non-condensing)
Ingress Protection	IP67

Dimensions

