

2MVIP-4KIR304X-C

4K Vandal-resistant Vari-focal Dome Network Camera



Features

Optics:

- Day/night functionality
- Smart IR, up to 30m (98 ft) IR distance
- Up to 120 dB Optical WDR(Wide Dynamic Range)
- 2D/3D DNR (Digital Noise Reduction)

Compression:

- Ultra 265,H.265, H.264, MJPEG
- Embedded smart algorithm Triple streams
- ROI (Region of Interest) 9:16 corridor mode
- Customized OSD

Network:

- ONVIF Conformance

Structure:

- Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- Wide voltage range of $\pm 25\%$
- IK10 vandal resistant IP67
- 3-Axis
- IP67

Specifications

CAMERA					
Sensor	1/2.5", progressive scan ,8.0 megapixel, CMOS				
Lens	2.8~12 mm@F1.6				
DORI Distance	Lens	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8mm	77.8	31.1	15.6	7.8
	12mm	333.3	133.3	66.7	33.3
Angle of View(H)	79.6°			34.9°	
Angle of View (V)	64°			16.6°	
Angle of View (O)	135°			42.9°	
Adjustment angle	Pan: 0°~360°		Tilt: 0°~90°		Rotate: 0°~360°
Shutter	Auto/Manual, 1~1/100000s				
Minimum Illumination	Colour: 0.02 Lux (F1.6, AGC ON) 0Lux with IR				
IR Range	Smart—IR, up to 30m (98 ft) IR range				
Day/Night	IR—cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	> 55dB				
WDR	120dB				
VIDEO					
Video Compression	Ultra265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 8MP (3840×2160): Max. 30 fps, 2MP (1920×1080): Max. 30 fps; Sub Stream: 2MP (1920×1080): Max. 30 fps; Third Stream: D1 (720×576): Max. 30 fps				
HLC	Supported				
BLC	Supported				
9:16 Corridor Mode	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
SMART					
Behavior Detection	Intrusion, cross line, motion detection				

2MVIP-4KIR304X-C

4K Vandal-resistant Vari-focal Dome Network Camera

Intrusion	Enter and loiter in a pre-defined virtual region
cross line	Cross a pre-defined virtual line
motion detection	Moving within a pre-defined virtual region
Recognition	Face detection. Audio detection
Intelligent Identification	Defocus, Scene Change, Object Left, Object Moving
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
AUDIO	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
STORAGE	
Edge Storage	Micro SD, up to 128 GB
Network Storage	ANR
NETWORK	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF (Profile S, Profile G), API
INTERFACE	
Audio I/O	Audio cable
	Input: impedance 35 kK; amplitude 2 V [p-p]
	Output: impedance 600 K; amplitude 2 V [p-p]
Alarm I/O	1/1
Network	1 RJ45, 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 K; amplitude 1 V [p-p]
Power Output	DC12V Power Output With PoE
GENERAL	
Power	12 V DC±25%, PoE (IEEE802.3 af)
	Power consumption: Max 8.7W
Dimensions (Ø x H)	148 x 111.3 mm (Ø5.8" x 4.4")
Weight	0.92 kg (2.0 lb)
Working Environment	-40°C ~ +60°C (-40°F ~ 140°F), Humidity:10%~95% RH (non-condensing)
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported

Dimensions

