

2MBIP-4KIR1004XVUA-C

4K WDR Ultra—HD Vari—focal Bullet Network Camera



Features

Optics:

- Day/night functionality
- Smart IR, up to up to 100m (328 ft) IR distance
- Up to 120 dB Optical WDR(Wide Dynamic Range)
- 2Df3D DNR (Digital Noise Reduction)
- Optical glass window with higher light transmittance

Compression:

- Ultra 265,H.265, H.264, MJPEG
- Embedded smart algorithm
- Triple Streams
- ROI (Region of Interest)
- 9:16 corridor mode
- Customized OSD

Network:

- ONVIF Conformance

Structure:

- Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- Wide voltage range of $\pm 25\%$
- IP67

Specifications

CAMERA					
Sensor	1/2.5", progressive scan, 8.0 megapixel, CMOS				
Lens	2.8~12mm@F1.6, P—Iris, AF automatic focusing and motorized zoom lens				
DORI Distance	Lens	Detect (m)	Observe (m)	Recognize (m)	Identify(m)
	2.8mm	77.8	31.1	15.6	7.8
	12mm	333.3	133.3	66.7	33.3
Angle of View (H)	79.6°			34.9°	
Angle of View (V)	64°			16.6°	
Angle of View (O)	103.5°			42.9°	
Shutter	Auto/Manual, 1/6 ~1/100000 s				
Minimum Illumination	Colour: 0.01 Lux (F1.6, AGC ON) 0 Lux with IR on				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	> 55dB				
IR Range	Smart—IR ,up to 100m (328ft) IR range				
Defog	Digital Defog				
WDR	120 dB				
VIDEO					
Video Compression	Ultra265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 8MP(3840×2160) : Max. 30 fps; 2MP (1920×1080): Max. 30 fps; Sub Stream: 2MP (1920×1080): Max. 30 fps; Third Stream: D1(720×576) : Max. 30fps				
9:16 Corridor Mode	Supported				
HLC	Supported				
BLC	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
SMART					
Behavior Detection	Intrusion, cross line, motion detection				
Intrusion	Enter and loiter in a pre—defined virtual region				
cross line	Cross a pre—defined virtual line				
motion detection	Moving within a pre—defined virtual region				
Recognition	Face detection.Audio detection				
Intelligent Identification	Defocus, Scene Change				
Statistical Analysis	People counting				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				

2MBIP-4KIR1004XVUA-C

4K WDR Ultra-HD Vari-focal Bullet Network Camera

AUDIO

Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ

STORAGE

Edge Storage	Micro SD, up to 128 GB
Network Storage	ANR

NETWORK

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF, API

INTERFACE

Audio I/O	Audio cable
	Input: impedance 35 kΩ; amplitude 2 V [p-p]
	Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	2 f 1
Serial Port	1 RS485
Network	1 RJ45, 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]

GENERAL

Power	12 V DC ± 25%, PoE (IEEE802.3 af)
	Power consumption: Max. 13.7W
Dimensions (L × W × H)	305.5 × 104.1 × 97.3mm (12.0" × 4.1" × 3.8")
Weight	1.65 kg (3.6 lb)
Working Environment	-40°C ~ +60°C (-40°F ~ 140°F), Humidity: 10%~95% RH (non-condensing)
Ingress Protection	IP67
Reset Button	Supported

INSTALLATION MODE

Wall mount	Mounting pedestal is included in the Product package
Ceiling mount	Mounting pedestal is included in the Product package
Rail mount	For outdoor rail installation
Pole mount	For outdoor pole installation

Dimensions

