

2MPIP-2MIR10022XUASL-C

2MP 22x Starlight Network Full Spectrum PTZ Dome Camera



Features

Optics

- Starlight illumination
- Accurate and fast focusing
- Full spectrum light with both white and infrared LED design
- Smart IR, up to 200 m (656 ft) IR distance
- Up to 120dB WDR(Wide Dynamic Range)
- While Light , up to 30m(98ft)

Compression

- Ultra 265,H.265, H.264, MJPEG
- Embedded smart algorithm
- Triple streams
- 1080P@60fps supported

Network

- ONVIF Conformance

Structure

- Innovative snow-removing functionality
- More effective heat dissipation system
- Intelligent temperature control technology
- 6 KV surge protection designed for network interface

Specifications

CAMERA	
Sensor	1/1.9", 2megapixel, progressive scan, CMOS
Lens	6.5 ~ 143 mm (22x optical zoom)
Angle of View (H)	70° (wide) ~ 3.76° (tele)
Shutter	Auto/Manual; shutter time: 1/6 s ~ 1/100000 s
Minimum Illumination	Colour: 0.001 lux (F1.5, AGC ON) 0 Lux with IR on
Iris	Auto/Manual; F1.5 ~ F3.4
Day/Night	IR-cut filter with auto switch (ICR)
S/N	> 52dB
WDR	120 dB
VIDEO	
Video Compression	Ultra 265,H.265, H.264, MJPEG
Max. Resolution	1920 × 1080
Frame Rate	1080P (1920×1080):Max.60 fps; 1080P (1920×1080):Max.15 fps;D1 (720×576):Max.8 fps 1080P (1920×1080):Max.60 fps;720P (1280×720):Max.30 fps;D1 (720×576):Max.15 fps
Video Streaming	Triple
HLC	Supported
Evaluative Metering	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
Digital Zoom	Supported
SMART	
Behavior Detection	Intrusion, crossing line, motion detection, Auto tracking
Exception Detection	Audio detection
Intelligent Identification	Face detection
Statistical Analysis	People counting
AUDIO	
Audio Compression	G.711
Two-way audio	Supported
STORAGE	
Edge Storage	Micro SD, up to 128 GB
NETWORK	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x
Compatible Integration	ONVIF, API
PAN & TILT	
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 240°/s Preset speed: 300°/s
Tilt Range	-15° ~ +90° (auto reverse)

2MPIP-2MIR10022XUASL-C

2MP 22x Starlight Network Full Spectrum PTZ Dome Camera

Tilt Speed	0.1° ~ 160°/s Preset speed: 240°/s
Number of Presets	256
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported
Drag-to-Zoom	Supported
INTERFACE	
Audio I/O	Audio cable
	Input: impedance 35 kΩ; amplitude 2 V [p-p]
	Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	2/ 1
Serial Port	1 RS485
Video Output	1 RJ45 10M/100M Base-TX Ethernet
Network	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
GENERAL	
Power	24 V AC (Default), 24 V DC
	Power consumption: 11 ~ 47W
Dimensions(Ø xH)	Ø 227x359.4 mm (Ø 8.9" x 14.2")
Weight	9.69 kg (21.4 lb)
Working Environment	40°C~70°C (-40°F ~ 158°F), Humidity: 10%~95% RH(non-condensing)
Ingress Protection	IP66
Weight	5.4 kg (11.9lb)
Working Environment	-40°C ~ +70°C (-40°F ~ 158°F), Humidity ≤ 95% RH (non-condensing)
ACCESSORIES	
Pendant mount	Ceiling plate is optional with different pendant rod for various applications
Standing pole mount	The interface is designed with internal G1½ screws. The screw depth must be more than 23 mm
Wall mount	/
Corner mount	/
Pole mount	/

Dimensions

