

# 2MPIP-2MIR15030XUA-POE-P

2MP 30x IR Network PTZ Dome Camera



## Features

### Optics

- 30X Optical Zoom
- Accurate and fast focusing
- Smart IR, up to 150 m (492ft) IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- 120dB true WDR

### Compression

- Ultra 265,H.265, H.264, MJPEG
- Embedded smart algorithm
- Triple streams
- Customized OSD

### Network

- ONVIF Conformance

### Structure

- Innovative snow-removing functionality
- More effective heat dissipation system
- Intelligent temperature control technology
- 6 KV surge protection designed for network interface
- IK10 vandal resistant
- IP66

## Specifications

8 KHZ	
<b>Sensor</b>	1/2.8", progressive scan,2.0megapixel, CMOS
<b>Lens</b>	4.5 ~ 135 mm , AF automatic focusing and motorized zoom lens
<b>Digital Zoom</b>	16
<b>Optical Zoom</b>	30

<b>DORI Distance</b>	Lens	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	4.5mm	69.8	27.9	14	7
	135mm	2094.8	837.9	419	209.5
<b>Angle of View (H)</b>	71.7°~ 2.4°				
<b>Angle of View (V)</b>	43.4°~1.3°				
<b>Angle of View (D)</b>	88.2°~2.8°				
<b>Shutter</b>	Auto/Manual; shutter time: 1 ~ 1/100000 s				
<b>Minimum Illumination</b>	Colour: 0.01 lux (F1.5, AGC ON) 0 lux with IR				
<b>Iris</b>	Auto/Manual; F1.5 ~ F4.0				
<b>Day/Night</b>	IR-cut filter with auto switch (ICR)				
<b>Digital noise reduction</b>	2D/3D DNR				
<b>S/N</b>	> 52dB				
<b>IR Range</b>	Up to 150 m (492 ft)				
<b>Defog</b>	Digital Defog				
<b>WDR</b>	120dB				
VIDEO					
<b>Video Compression</b>	Ultra 265,H.265, H.264, MJPEG				
<b>H.264 code profile</b>	Baseline profile, Main Profile, High Profile				
<b>Frame Rate</b>	Main Stream:2MP (1920×1080):Max. 30 fps; Sub Stream:2MP (1920×1080):Max. 30 fps; Third Stream: D1 (720×576): Max. 30 fps				
<b>HLC</b>	Supported				
<b>BLC</b>	Supported				
<b>EIS</b>	Supported				
<b>OSD</b>	Up to 8 OSDs				
<b>Privacy Mask</b>	Up to 24 areas				
<b>ROI</b>	Up to 8 areas				
<b>Motion Detection</b>	Up to 4 areas				
SMART					
<b>Behavior Detection</b>	Intrusion, cross line, motion detection, auto tracking				
<b>Intrusion</b>	Enter and loiter in a pre-defined virtual region				
<b>cross line</b>	Cross a pre-defined virtual line				
<b>motion detection</b>	Moving within a pre-defined virtual region				
<b>auto tracking</b>	Tracking the specified target				
<b>Recognition</b>	Face detection, Audio detection				
<b>Intelligent Identification</b>	Defocus, Scene Change, Object Left, Object Moving				
<b>Statistical Analysis</b>	People counting				
<b>General Function</b>	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
AUDIO					
<b>Audio Compression</b>	G.711				
<b>Two-way audio</b>	16 ~ 30W				

# 2MPIP-2MIR15030XUA-POE-P

2MP 30x IR Network PTZ Dome Camera

<b>Suppression</b>	Supported
<b>Sampling Rate</b>	8 KHZ
<b>STORAGE</b>	
<b>Edge Storage</b>	Micro SD, up to 128 GB
<b>Network Storage</b>	ANR
<b>NETWORK</b>	
<b>Protocols</b>	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
<b>Compatible Integration</b>	ONVIF(Profile S, Profile G), API
<b>PAN &amp; TILT</b>	
<b>Pan Range</b>	360° (endless)
<b>Pan Speed</b>	0.1°/s ~ 240°/s Preset speed: 300°/s
<b>Tilt Range</b>	-15° ~ +90° (auto reverse)
<b>Tilt Speed</b>	0.1° ~ 160°/s Preset speed: 240°/s
<b>Number of Presets</b>	1024
<b>Patrol</b>	Up to 16 patrols, up to 32 presets per patrol Note: The total number of patrols and patterns is 16.
<b>Home Position</b>	Supported
<b>INTERFACE</b>	
<b>Audio I/O</b>	Audio cable Input: impedance 35 kΩ; amplitude 2 V [p-p] Output: impedance 600 Ω; amplitude 2 V [p-p]
<b>Alarm I/O</b>	1/ 1
<b>Network</b>	10M/100M Base-TX Ethernet
<b>GENERAL</b>	
<b>Power</b>	24 V AC±25%, 24 V DC±25%,PoE (PSE Required) Power consumption: 9 ~ 42W
<b>Dimensions(Ø xH)</b>	Ø 227x359.4 mm (Ø 8.9" x 14.2")
<b>Weight</b>	5.28 kg (11.6lb)
<b>Working Environment</b>	-40°C ~ 65°C (-40°F ~ 149°F), Humidity:10%~95% RH (non-condensing)
<b>Ingress Protection</b>	IP66

## Dimensions

