



## Features

- Support H.265/H.264 video formats
- Support TVI,AHD, CVI,CVBS, IP cameras with adaptive access
- 8-channel BNC input
- Support 1-ch HDMI output, 1-ch VGA output at up to 1920\*1080
- Long transmission distance over coax cable

## Specifications

VIDEO/AUDIO INPUT	
<b>Analog Video Input</b>	8-ch, BNC
<b>IP Video Input</b>	4-ch(only IP up to 12ch),each channel up to 4K
	Support AHD input:
	8MP@15fps(channel1-channel2)
	5MP@20fps
	4MP@30fps
	3MP@30fps (channel1 –channel2)
	1080P@30fps 720P@60fps
<b>Supported Analog Camera Types</b>	Support TVI input: 8MP@15fps(channel1-channel2) 5MP@20fps 4MP@30fps 3MP@20fps (channel1 – channel2) 1080P@30fps 720P@60fps Support CVI input: 8MP@15fps(channel1-channel2) 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input
<b>Audio Input</b>	1-ch, RCA
<b>Two-way Audio</b>	1-ch, RCA
<b>Channel Associated Audio</b>	1-ch, RCA
NETWORK	
<b>Incoming Bandwidth</b>	40Mbps
<b>Outgoing Bandwidth</b>	64Mbps
<b>Remote Users</b>	128
<b>Protocols</b>	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
VIDEO/AUDIO OUTPUT	
<b>CVBS Output</b>	1-ch, BNC
<b>VGA Output</b>	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
<b>HDMI Output</b>	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
<b>Audio Output</b>	1-ch, RCA
<b>Synchronous Playback</b>	8-ch
ENCODING	
<b>Recording Resolution</b>	8MP Lite/5MP Lite/4MP Lite/3MP/1080P/960P/720P/960H/4CIF/CIF
<b>Recording Frame Rate</b>	Main stream: 8MP Lite@8fps (channel1-channel2) 5MP Lite@12fps 4MP Lite@15fps 3MP@15fps(channel1 – channel2) 2MP@15fps 720P@30fps Sub stream: D1@30fps(Max)

## Dimensions

HARD DISK	
<b>SATA</b>	1 SATA interfaces
<b>Capacity</b>	Up to 10TB for each HDD
EXTERNAL INTERFACE	
<b>Network Interface</b>	1RJ45 10M/100M self-adaptive Ethernet Interface
<b>USB Interface</b>	Rear panel: 2 x USB2.0
<b>Serial Interface</b>	1 x RS485
GENERAL	
<b>Power Supply</b>	12V DC
<b>Power Consumption</b>	≤ 8 W(without HDD)
<b>Working Temperature</b>	-10°C ~ + 55°C ( +14°F ~ +131°F )
<b>Working Humidity</b>	≤ 90% RH(non-condensing)
<b>Dimensions(W×D× H)</b>	260 x 240 x 46 (mm) (10.2" × 9.4"×1.8")
<b>Weight (without HDD)</b>	≤1.1 Kg ( 4.19lb )

