



## Specifications

| CAMERA                       |                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------|
| <b>System</b>                | NTSC                                                                                       |
| <b>Sensor</b>                | IMX415 1/2.8                                                                               |
| <b>DSP</b>                   | FH8556                                                                                     |
| <b>Active Pixel</b>          | 3840 x 2160                                                                                |
| <b>Sync.</b>                 | Internal                                                                                   |
| <b>Resolution</b>            | 8MP                                                                                        |
| <b>Video Out</b>             | TVI: 8M@15fps, 8M@12.5fps<br>AHD: 8M@15fps<br>CVI: 8M@15fps, 8M@12.5fps<br>CVBS: PAL, NTSC |
| <b>Minimum Illumination</b>  | 0.01Lux(F1.2)                                                                              |
| <b>Gama adjust</b>           | 0.45                                                                                       |
| <b>S/N Ratio</b>             | 50dB(min)(AGC closed)                                                                      |
| <b>AE</b>                    | GLOBE/BLC                                                                                  |
| <b>AWB</b>                   | PRO/GRAY WORLD/ATW/MWB                                                                     |
| <b>3DNR</b>                  | AUTO/MANUAL(0-10)                                                                          |
| <b>OSD</b>                   | Yes                                                                                        |
| <b>Language</b>              | Eng, Chin1, Chin2, Pycc, ESPA, FRAN, POL, ITAL, PORT, JAPA                                 |
| <b>Day/Night</b>             | Auto, Color, MONO, Ext                                                                     |
| <b>Power Input</b>           | DC12V±1V                                                                                   |
| <b>Power Dissipation</b>     | 175mA-180mA                                                                                |
| <b>Transmission distance</b> | 75-5 300M                                                                                  |
| <b>Operation Temperature</b> | Temperature -10°C+55°C, Humidity less than 85%RH                                           |
| <b>Weight</b>                | 1.65 lbs                                                                                   |
| <b>Color</b>                 | White+black                                                                                |

## Features

### Features:

- 4-in-1 bullet camera
- 1/2.8" Sony 415 CMOS 8.0M+FH8556
- 18pcs SMD LEDs
- 20m IR Range
- Standard match 2.8mm lens
- With WDR
- Default TVI output