



Features

- 4-in-1 bullet camera
- 1/2.8" IMX 307 CMOS 2.0M + FH8550M
- 30pcs SMD LEDs
- 40m IR Range
- Standard match 2.8-12mm motorized lens
- WDR
- Default TVI output

Specifications

GENERAL	
Power System	NTSC
Sensor	IMX307 1/2.8
DSP	FH8550M
Active Pixel	1920 x 1080
Sync.	Internal
Resolution	1080P
Video Out	A/C/T/CVBS
Minimum Illumination	0.0001Lux(F1.2)
Gama Adjust	0.45
AF Mode	SEMI/AUTO/MANUAL
Electric Shutter	1/30s-1/10000s
S/N Ratio	50dB(min)
AE	GLOBE/BLC
WB	ATW/MWB
WDR	EXT/OPEN/CLOSE
3DNR	AUTO/MANUAL(0-30)
OSD	Yes
Language	Eng Chin1/2 Russ Ital Spain Franc POL Port JAPA
Day/Night	Auto, Color, B/W, Ext
Power Input	DC12V±1V
Power Dissipation	95mA-105mA
Transmission Distance	75-5 300M
Operation Temperature	Temperature -10°C+55°C, Humidity less than 85%RH
Weight	0.85 lbs
Color	White+ black