



## Features

- SONY IMX307 2MP starlight CMOS, capture moving images.
- Hybrid Coaxial high-definition output, Excellent performance, clear and bright picture
- Lux: 0.001 Lux @ (F1.2,AGC ON) 0 LUX with IR
- Supports AF port
- IR-CUT switch, CDS external control , D/N mode
- OSD menu ,suitable for user-defined settings
- WDR , DWDR, 2D-DNR, 3D-DNR
- UTC function

## Specifications

CAMERA	
<b>Sensor</b>	1/2.9" Sony IMX307
<b>System</b>	PAL/NTSC
<b>Effective Pixel</b>	1920(H)x1080(V)
<b>Lens</b>	2.8mm Fixed
<b>IR Range</b>	20m
<b>Illumination</b>	0.001Lux@(F1.2,AGC ON) 0LUX with IR
<b>Shutter</b>	AUTO
<b>D/N</b>	EXT (Default) / AUTO / COLOR / B/W
<b>Synchronously</b>	Internal
<b>FPS</b>	1080P@25fps / 1080P@30fps
<b>Video Output</b>	AHD/TVI/CVI/CVBS (Optional)
OSD MENU	
<b>AF</b>	AF Mode / Zoom / Boot Mode / TDN AF / One Key Focus / Lens Init /Reset
<b>Exposure</b>	BLC/Global
<b>Back-Light Mode</b>	f/ / Back-light / HSBLC
<b>W/B Mode</b>	AWB /Manual
<b>D/N Mode</b>	Ext/Auto/Color/B&W
<b>Adjust</b>	Contrast/Sharpness / Saturation /3D-DNR
<b>Video Setting</b>	Coaxial HD/D-WDR/NTSC&PAL
<b>Exit</b>	Save & End / Reset / Not-save
GENERAL	
<b>Working Temperature</b>	-20°C to 60°C
<b>Working Humidity</b>	Relative humidity <90 %
<b>Power</b>	DC12V