

2MVT-2MIR40ZSL

2MP Outdoor Dome Camera with Starlight



Features :

- 1/2.8" 2 mega Pixel CMOS Sensor
- Resolution: Digital: 1920Hx1080P, NTSC / PAL
- Motion Detection
- dWDR
- 2.8-12mm Motorized Lens Auto Focus
- True Day & Night (ICR)
- Video Output-TVl
- Built-in IR LED 42 pcs (Night View Distance Indoor 40/ Outdoor 30m)
- External Control (Focus/Zoom, OSD)

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.8" 2 Mega Pixel CMOS Sensor
Resolution	Digital: 2048 x 1536, NTSC / PAL
Signal	PAL / NTSC
Min. Illumination	0.0001Lux @ (F1.2,AGC ON), 0LUX with IR
Day & Night System	ICR
Shutter Speed	AUTO
Wide Dynamic Range	D-DWR
Scanning System	Progressive
Digital Noise Reduction	2DNR / 3DNR
S/N Ratio	> 50dB (AGC off)
Lens	2.8-12mm Motorized Lens Auto Focus
IR LED	42 units
Video Output	TVI
Night View Distance	Indoor 40/ Outdoor 30m
AGC	1 - 5 Levels
IMAGE	
Resolution	1920(H) x 1080(V)
Day & Night	Auto/ Color/ B&W/ Ext
White Balance	ATW/ Manual/ AWC Push
Backlight	Close/Back-light Compensation/Strong Inhibition
Mirror	Off/ H/ V/ H&V/ Rotate
HLC	On/ Off
LSC	Off/ On
Privacy Zone	2 Areas
Motion	Off/ On
GENERAL	
Power Consumption	DC12V / 1 Amp
Operating Temperature	-4°F to 140°F (-20°C to 60°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	Relative humidity < 90 %
IP Rating	IP-66