



Features

- Full height turnstiles
- Outer casing is made with a durable 304 stainless steel
- Supports input way: Two-side card reader, paper ticket, fingerprint, coins.
- Infrared light detecting, Alarming when illegal infiltration or tailing
- Clamping avoid
- Working mode and opening time is adjustable
- Non-contact detection, abnormal body temperature warning system
- Supports body temperature detection and personnel information binding, which can quickly confirm personnel information and scan body temperature
- Built-in deep learning dedicated chip, Supportsss local off-line recognition, 10,000 face capacity, face whitelist (1:N)
- Fastest recognition time 0.2 seconds, various model merge mode are used to reduce false rate and increase pass rate
- WDR, 2MP (1080P) low illumination wide-angle camera and F1.6 large aperture lens for capturing high quality image with various complex lighting scenes
- Supports anti-spoofing detection based on a deep learning algorithm, effective against fraud, it can differentiate between a live person and a photograph or video.

Specifications

GATE FEATURE	
Turnstile Type	Double full height turnstile
Cabinet Material	304 stainless steel (standard)
	316 stainless steel (optional)
Finish	Stainless steel satin finish
Safety	Fail-safe (free exit/entry)
Number of wings (angle)	X type-4 (90°)
	Y type-3 (120°)
Dimension (L*W*H)	2400 x 1500 x 2250 (mm)
	94.49" x 59.06" x 88.58" (in)
Direction	Single / bidirectional
Power Supply	AC110–220V, 50/60Hz
Flow Rate	50 person/min
Working Environment	Indoor & outdoor
Unlock Mode	Solenoid (standard)
	Motor drive(optional)
Motor	DC brush motor (standard)
	DC brushless motor (optional)
	DC servo motor (optional)
FACIAL RECOGNITION	
Operation System	Linux
Face Recognition Accuracy Rate	>99%
Face Recognition Time	200ms
Face Capacity	10,000
Card Capacity	100,000
Storage Capacity	4GB
Event Capacity	30,000 (with images)
Measurement Range	86°F - 113°F [30°C - 45°C]
Measurement Accuracy	0.1°C
Measurement Deviation	≤ ±0.3°C
Measurement Distance	39.37" (in) [1m]

Authentication Mode	Face Whitelist: (1:N)
	Card:(1:N)
	Face +Body temperature
Card Type	Mifare 1 Card
User Management	Supportss user library addition, deletion, update
Record Management	Supportss local recording and real-time upload
Interface	LAN×1, Wiegand Input×1, Wiegand Output×1, RS485×1, Alarm Input×2, Alarm Output×1, USB2.0×1, Lock×1, Door Contact ×1, Exit Button×1
Power Supply	Input 12V±25% DC
Screen	Touch Screen, Size: 7 inch, Resolution: 600×1024
Camera	Dual Lens, 2MP, 1080P
Supplement Light	LED soft light and infrared light
Dimensions (L×W×H)	134 x 33 x 305 (mm) 5.28" x 1.3" x 12" (in)
Working Environment	For access control terminal: -20℃~+65℃, Relative Humidly<95% (non-condensing)
Protection Level	Both terminal and module: IP 54
Application Situation	Indoor, No wind



Options Available with this Model

MODEL	2MFHT-6		
MOTOR TYPE	SEMI AUTOMATIC	AUTOMATIC	BRUSHLESS
Control Model	Electromagnetic	Brush Motor	Brushless Motor
Drive Type	Push By Hand	Drive By Motor	Drive By Motor
Power On	Pick Up Arm By Hand	Pick Up Arm By Motor	Pick Up Arm By Motor
Max Flow Per Day	500	1000	2000
Life Time	2-3 Years	3-5 Years	At Least 5 Years
MTBF	3 Million	5 Million	10 Million
Controller	Standard Function Can Be Set	Full Function Can Be Set	Full Function Can Be Set
Structure	Simple	Stable	Strong
Mechanical Friction	Mechanical Shock	Yes	Small
Noise	Moderate	Quiet	Almost None
After Service	Electromagnetic (Perishable)	Low	Low