



Features

- Full height turnstiles
- Stainless steel 304#
- Support input way: Two-side card reader, paper ticket, fingerprint, coins.
- Infrared light detecting, Alarming when illegal infiltration or tailing
- Clamping avoid
- Working mode and opening time is adjustable
- Support non-contact detection, support warning people with abnormal body temperature
- Support body temperature detection and personnel information binding, which can quickly confirm personnel information and do body temperature detection
- Built-in deep learning dedicated chip, supports local off-line recognition, 10,000 face capacity, face whitelist (1:N)
- Fastest recognition time 0.2 seconds, various model merge mode are used to reduce false rate and increase pass rate
- WDR, 2MP (1080P) low illumination wide-angle camera and F1.6 large aperture lens for capturing high quality image with various complex lighting scenes
- Support anti-spoofing detection based on deep learning algorithm, effective against fraud such as photo and video

Specifications

GATE FEATURE	
Turnstile type	Double full height turnstile
Cabinet material	304 stainless steel (standard)
	316 stainless steel (optional)
Finish	Stainless steel satin finish
Safety	Fail-safe (free exit/entry)
Dimension	1500 x 1500 x 2250 mm 59.06" x 59.06" x 88.58" (in)
Direction	Single / bidirectional
Power supply	AC110-220 V, 50/60Hz
Flow rate	50 person/min
Working environment	Indoor & outdoor
Unlock Mode	Solenoid(standard)
	Motor drive(optional)
Motor	DC brush motor (standard)
	DC brushless motor (optional)
	DC servo motor (optional)
FACIAL RECOGNITION	
Operation System	Linux
Face Recognition Accuracy Rate	>99%
Face Recognition Time	200ms
Face Capacity	10,000
Card Capacity	100,000
Storage Capacity	4GB
Event Capacity	30,000 (with images)
Measurement Range	30°C - 45°C
Measurement Accuracy	0.1°C
Measurement Deviation	≤ ±0.3°C
Measurement Distance	1m
Authentication Mode	Face Whitelist: (1:N)
	Card:(1:N)
	Face + Body temperature
Card Type	Mifare 1 Card

User Management	Support user library addition, deletion, update
Record Management	Support local recording and real-time upload
Interface	LAN×1, Wiegand Input×1, Wiegand Output×1, RS485×1, Alarm Input×2, Alarm Output×1, USB2.0×1, Lock×1, Door Contact ×1, Exit Button×1
Power Supply	Input 12V±25% DC
Screen	Touch Screen, Size:7 inch, Resolution: 600×1024
Camera	Dual Lens, 2MP, 1080P
Supplement Light	LED soft light and infrared light
Dimensions (L×W×H)	134.0mm×33.0mm×305.0mm
Working Environment	For access control terminal: -20°C~+65°C, Relative Humidity<95% (non-condensing)
Protection Level	Both terminal and module: IP 54
Application Situation	Indoor, No wind



Options Available with this Model

MODEL	2MFHT-7
MOTOR TYPE	BRUSHLESS
Control Model	Brushless Motor
Drive Type	Drive By Motor
Power On	Pick Up Arm By Motor
Max Flow Per Day	2000
Life Time	At Least 5 Years
MTBF	10 Million
Controller	Full Function Can Be Set
Structure	Strong
Mechanical Friction	Small
Noise	Almost None
After Service	Less