



Features

- Vertical Swing turnstile, Stainless steel 304#
- Size: 55.1" x 7.9" x 39.4" (in); Gross weight: single: 70kg, double: 95kg
- Unlock time: 0.2s ;
- Pass rate: 35 person /min;
- Pass width: ≤550mm;
- Input :100V~240V;
- Driving voltage: 24v;
- Environment: -25~ +70;
- Power consumption: 30w;
- Input: 12v dry contact; 6pair Infrared sensor.
- Automatic open when power off
- Support non-contact detection, support warning people with abnormal body temperature
- Support body temperature detection and personnel information binding, which can quickly confirm personnel information and do body temperature detection
- Built-in deep learning dedicated chip, supports local offline recognition, 10,000 face capacity, face whitelist (1:N)
- Fastest recognition time 0.2 seconds, various model merge mode are used to reduce false rate and increase pass rate
- WDR, 2MP (1080P) low illumination wide-angle camera and F1.6 large aperture lens for capturing high quality image with various complex lighting scenes
- Support anti-spoofing detection based on deep learning algorithm, effective against fraud such as photo and video

Specifications

GATE FEATURE	
Turnstile type	speed gate turnstile
Cabinet material	304 stainless steel (standard)
	316 stainless steel (optional)
Arm material	Acrylic (optional)
	Tempered glass (optional)
Finish	Stainless steel satin finish
Function	Fail-safe, anti-clamping
Dimension	55.1" x 7.9" x 39.4" (in)
Passage width	Customized
Direction	Single / bidirectional
Power supply	AC110~220 V, 50/60Hz
Unlock time	Adjustable
Working environment	Indoor
Indicator lights	Yes
Motor	DC brush motor (standard)
	DC brushless motor (optional)
	DC servo motor (optional)
FACIAL RECOGNITION	
Operation System	Linux
Face Recognition Accuracy Rate	>99%
Face Recognition Time	200ms
Face Capacity	10,000
Card Capacity	100,000
Storage Capacity	4GB
Event Capacity	30,000 (with images)
Measurement Range	30°C - 45°C
Measurement Accuracy	0.1°C
Measurement Deviation	±±0.3°C
Measurement Distance	1m

Authentication Mode	Face Whitelist: (1:N)
	Card:(1:N)
	Face + Body temperature
Card Type	Mifare 1 Card
User Management	Support user library addition, deletion, update
Record Management	Support local recording and real-time upload
Interface	LAN×1, Wiegand Input×1, Wiegand Output×1, RS485×1, Alarm Input×2, Alarm Output×1, USB2.0×1, Lock×1, Door Contact ×1, Exit Button×1
Power Supply	Input 12V±25% DC
Screen	Touch Screen, Size:7 inch, Resolution: 600×1024
Camera	Dual Lens, 2MP, 1080P
Supplement Light	LED soft light and infrared light
Dimensions (L×W×H)	134.0mm×33.0mm×305.0mm
Working Environment	For access control terminal: -20°C~ +65°C, Relative Humidity<95% (non-condensing)
Protection Level	Both terminal and module: IP 54
Application Situation	Indoor, No wind



Options Available with this Model

MODEL NUMBER	2MGST-5 (SINGLE FLAP)			2MGST-5D (DOUBLE SIDED FLAPS)		
	BRUSH MOTOR	BRUSHLESS MOTOR	SERVO MOTOR	BRUSH MOTOR	BRUSHLESS MOTOR	SERVO MOTOR
Drive Type	Drive By Brush Motor	Drive By Brushless Motor	Drive By Servo Motor	Drive By Brush Motor	Drive By Brushless Motor	Drive By Servo Motor
Arm Material	Acrylic	Acrylic / Tempered Glass	Acrylic / Tempered Glass	Acrylic	Acrylic / Tempered Glass	Acrylic / Tempered Glass
Power Off	Automatic Open	Automatic Open	Automatic Open	Automatic Open	Automatic Open	Automatic Open
Lane Width	0-23.6" (in) [0-600mm]	0-35.4" (in) [0-900mm]	0-35.4" (in) [0-900mm] or Longer	0-35.4" (in) [0-900mm] or Longer	0-35.4" (in) [0-900mm] or Longer	0-35.4" (in) [0-900mm] or Longer
Speed	1 Second Not Adjustable	0.5 Seconds Adjustable	Max 0.2 Second And Can Adjustable	1 Second Not Adjustable	0.5 Seconds Adjustable	Max 0.2 Second And Can Adjustable
Max Capacity Flow	1000	2000	More Than 2000	1000	2000	More Than 2000
Life Time	2-3 Years	3-5 Years	At Least 5 Years	2-3 Years	3-5 Years	At Least 5 Years
MTBF	5 Million	10 Million	20 Million	5 Million	10 Million	20 Million
Controller	Standard Function Can Be Set	Standard Function Can Be Set	Full Function Can Be Set	Standard Function Can Be Set	Standard Function Can Be Set	Full Function Can Be Set
Structure	Stable	Strong	Strong	Stable	Strong	Strong
Mechanical Friction	Yes	Some	None	Yes	Some	None
Noise	Moderate	Quiet	Almost None	Moderate	Quiet	Almost None