



Features:

Optics

- Thermal & Optical dual-spectrum image, dual video with single IP address, adaptable to more various scenes
- Starlight illumination

Smart

- Screens for body temperature and should be used in conjunction with the black-body
- Face detection
- Collects a library of mask and human body temperature attributes
- Notifies user when no mask is detected and/or if abnormal temperature are detected
- Notification are both visual and audible

Compression

- Ultra 265, H.265, H.264, MJPEG
- Triple streams
- Max 2688*1520@60fps in the optical module
- Max 720P@25fps in the thermal module

Network

- ONVIF conformance

Structure

- DC12V or PoE power supply
- Wide voltage range of $\pm 25\%$ in DC
- Micro SD, up to 256 GB
- Alarm 2 in and 2 out, Audio 1 in and 1 out
- IP66

Specifications

OPTICAL MODULE	
Sensor	1/1.8", 4MP progressive scan CMOS
Lens	6mm@F1.6,
Iris	Fixed Iris
Angle of View (H)	56.1°
Angle of View (V)	31.7°
Frame Rate	4MP (2688 x 1520), Max 60fps
Shutter	Auto/Manual, 1 ~ 1/100000s
Min. Illumination	Color: 0.001lux (F1.6, AGC ON); 0 lux with IR
WDR	120dB
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 50m (164 ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
BLC	Supported
THERMAL MODULE	
Sensor type	Vanadium Oxide Uncooled Focal Plane Arrays
Max. Resolution	384 x 288
Angle of View (H)	39.0°
Angle of View (V)	29.6°
Frame Rate	720P(1280*720), Max 25fps
Response Waveband	8~14μm
Pixel Size	17μm
IFOV	1.75mrad
NETD	≤40mk @ f1.0 @23±3°C
Lens (Focal Length)	10mm @F1.0
Palette	Up to 20 palettes of optional color, including: white hot, lava, iron oxide red, hot iron, medical, arctic, rainbow 1, rainbow 2, rainbow 3, depict hot, ice hot, black hot, mazarine, fusion, red hot, green hot, color 1, color 2, rain, puce
TEMPERATURE SCREENING ACCURACY	
Temperature Range	30°C~42°C
Temperature Accuracy	±0.3 (with black-body), without black-body is not Supported
Temperature Screening Working Environment	16°C~32°C
SMART	
Human body Temperature screening	Supports human body temperature screening when OSD displays the temperature on the body surface or inside Supports human body temperature screening alarm, and set alarm threshold temperature
Audio and light alarm	Supports audio and light warning function, with red and blue warning lights built in

Face detection	Optical camera supports face detection
Attribute collection	Supports mask and human body temperature attribute collection
Alarm	Supports alarm when no mask and abnormal temperature are detected
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
VIDEO	
Compression	Ultra 265, H.265, H.264, MJPEG
Video Stream	Triple streams
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas (8 blacks)
AUDIO	
Audio Compression	G.711U, G.711A
Two-way audio	Supported, Built in mic and speaker
Sampling Rate	8KHZ
STORAGE	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
NETWORK	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS,
Compatible Integration	ONVIF (Profile S, Profile G)
Web Browser	Plug-in required for live view: IE®9+, Chrome® 41 and below, Firefox® 52 and below
INTERFACE	
Audio I/O	Audio cable
	1 Input: impedance 35kΩ; amplitude 2V [p-p]
	1 output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	2/2
Serial Port	1 RS485
Network	1 x RJ45 10M/100M Base-TX Ethernet
GENERAL	
Power	DC 12V(±25%), PoE+(IEEE802.3at)
	Power consumption: Max 14W
	Supports reverse polarity protection, Over voltage and current surge protection, Input short circuit protection
Dimensions (Ø x H)	Ø 395.2mm x 137.0mm x 112.0mm (Ø 15.6"x 5.4"x 4.4")
Net Weight	3.5kg (7.7lb)
Installation method	Tripod
Ingress Protection	IP66

Dimensions

