



## Specifications

GATE FEATURE	
<b>Turnstile type</b>	speed gate turnstile
<b>Cabinet material</b>	304 stainless steel (standard)
	316 stainless steel (optional)
<b>Arm material</b>	Acrylic (optional)
	Tempered glass (optional)
<b>Finish</b>	Stainless steel satin finish
<b>Function</b>	Fail-safe, anti-clamping
<b>Dimension</b>	47.2" x 11" x 39.4" (in)
<b>Passage width</b>	Customized
<b>Direction</b>	Single / bidirectional
<b>Power supply</b>	AC110-220 V, 50/60Hz
<b>Unlock time</b>	Adjustable
<b>Working environment</b>	Indoor
<b>Indicator lights</b>	Yes
<b>Motor</b>	DC brush motor (standard)
	DC brushless motor (optional)
	DC servo motor (optional)
FACIAL RECOGNITION	
<b>Operation System</b>	Linux
<b>Face Recognition Accuracy Rate</b>	>99%
<b>Face Recognition Time</b>	200ms
<b>Face Capacity</b>	10,000
<b>Card Capacity</b>	100,000
<b>Storage Capacity</b>	4GB
<b>Event Capacity</b>	30,000 (with images)
<b>Measurement Range</b>	30°C - 45°C
<b>Measurement Accuracy</b>	0.1°C
<b>Measurement Deviation</b>	±0.3°C
<b>Measurement Distance</b>	1m

## Features

- Stainless steel 304#, 2 channel bridge
- Anti-clamping function
- Working mode and opening time is adjustable
- Alarm will activate when it detects infiltration or tailing
- LED direction guide
- Working temperature: -30+80
- Working humidity: 5% - 90%
- Passage width: max 600mm
- Wing will open automatically when power off
- Non-contact detection, warns of people with abnormal body temperature
- Supports body temperature detection and personnel information binding, which can quickly confirm personnel information and do body temperature detection
- Built-in deep learning dedicated chip, supports local off line recognition, 10,000 face capacity, face white list (1:N)
- Fastest recognition time 0.2 seconds, various model merge mode are used to reduce false rate and increase pass rate
- WDR, 2MP (1080P) low illumination wide-angle camera and F1.6 large aperture lens for capturing high quality image with various complex lighting scenes
- Anti-spoofing detection based on deep learning algorithm, can identify the difference between an actual person and a picture or video.

<b>Authentication Mode</b>	Face Whitelist: (1:N)
	Card:(1:N)
	Face +Body temperature
<b>Card Type</b>	Mifare 1 Card
<b>User Management</b>	Support user library addition, deletion, update
<b>Record Management</b>	Support local recording and real-time upload
<b>Interface</b>	LAN×1, Wiegand Input×1, Wiegand Output×1, RS485×1, Alarm Input×2, Alarm Output×1, USB2.0×1, Lock×1, Door Contact ×1, Exit Button×1
<b>Power Supply</b>	Input 12V±25% DC
<b>Screen</b>	Touch Screen, Size:7 inch, Resolution: 600×1024
<b>Camera</b>	Dual Lens, 2MP, 1080P
<b>Supplement Light</b>	LED soft light and infrared light
<b>Dimensions (L×W×H)</b>	134.0mm×33.0mm×305.0mm
<b>Working Environment</b>	For access control terminal: -20°C~ +65°C, Relative Humidity<95% (non-condensing)
<b>Protection Level</b>	Both terminal and module: IP 54
<b>Application Situation</b>	Indoor, No wind



### Options Available with this Model

MODEL NUMBER	2MWT-2 (SINGLE FLAP)		2MWT-2 (DOUBLE SIDED FLAPS)	
	BRUSH	BRUSHLESS	DOUBLE SIDED BRUSH MOTOR	DOUBLE SIDED BRUSHLESS MOTOR
<b>Drive Type</b>	Drive By Brush Motor	Drive By Brushless Motor	Drive By Brush Motor	Drive By Brushless Motor
<b>Arm Material</b>	Acrylic	Acrylic / Tempered Glass	Acrylic	Acrylic / Tempered Glass
<b>Power Off</b>	0-23.6" (in) [0-600mm]	0-35.4" (in) [0-900mm]	0-23.6" (in) [0-600mm]	0-35.4" (in) [0-900mm]
<b>Lane Width</b>	Automatic Open	Automatic Open	Automatic Open	Automatic Open
<b>Speed</b>	1 Second Not Adjustable	0.5 Seconds Adjustable	1 Second Not Adjustable	0.5 Seconds Adjustable
<b>Max Capacity Flow</b>	1000	2000	1000	2000
<b>Life Time</b>	2-3 Years	3-5 Years	2-3 Years	3-5 Years
<b>MTBF</b>	5 Million	10 Million	5 Million	10 Million
<b>Controller</b>	Standard Function Can Be Set	Standard Function Can Be Set	Standard Function Can Be Set	Standard Function Can Be Set
<b>Structure</b>	Stable	Strong	Stable	Strong
<b>Mechanical Friction</b>	Yes	Some	Yes	Some
<b>Noise</b>	Moderate	Quiet	Moderate	Quiet