



Features

- Normal-speed of open / close: 2~6 sec. adjustable
- Octagonal crank arm with rubber & LED light bar, length following (or Max.11.5' feet round arm):
 - 2~3 sec. / Max. 13.1' ft
 - 4~6 sec. / Max. 16.4' ft
- Includes of arm x1, remote x2, air switch x1, push button x1 to open/close barrier
- Boom bracket and power supply for LED bar is sold separately
- Housing color optional: yellow (default)/orange/white/red/blue
- Arm direction left/right exchangeable without changing any parts

Specifications

GATE FEATURE	
Power Supply	AC 85~264V, 50~60HZ, 50W
Motor	50W DC-24V brushless servo torque motor 10 million MTBF, 100% duty cycle
Remote (Optional)	Distance > 65.6' ft
Spring	1~3 pcs. spring balance
Controller	80C51 MCU, 20MHz, PWM variable frequency servo controller board
Loop Detector Input	pulse width 100 > ms
IR Detector Input	pulse width 100 > ms
Up & Down Input	pulse width 100 > ms
Traffic Light Output	AC220V output power (passive), current Max. 3A/AC220V
Loop Detector Syn. Output	Relay NO output,; Current Max.0.5A/AC220V, or Max. 1A/DC12V
RS485 interface	9600bps, ASCII decimal encoded
Arm	Octagonal crank arm with rubber & LED light bar, length following (or Max. 11.5' feet round arm): 2~3 sec. / Max. 13.1' ft 4~6 sec. / Max. 16.4" feet
Housing	2mm cold-roller sheet, IP54
Housing Size (HxWxD)	950 x 320 x 329 (mm) / 37.4" x 12.5" x 12.9" (in)
Package Size	1100 x 480 x 430 (mm) / 43.3" x 18.8" x 16.9" (in)
Gross Weight	~ 46kg / 101lb
Operating Temperature	-30°C to 55°C / -22°F to 131°F
Humidity	10%-95%