

2MEP16-IP4M22X

4MP IP PTZ Dome Starlight Camera 22x with
Stainless Steel Explosion proof Housing – 316L Stainless Steel



Features

- 316L Stainless steel
- Certificate Mark: Exd II C T6 Gb/Ext DA21 IP68 T80°C
- Protection enclosure: IP68
- Starlight illumination
- 22x optical zoom
- Accurate and fast focusing
- Ultra 265, H.265, H.264, MJPEG
- Triple streams
- Embedded smart algorithm
- Customized OSD
- ONVIF Conformance
- Intelligent temperature control technology
- 6 KV surge protection designed for network interface

HOUSING					
Atmospheric Pressure	80KPa ~ 106Kpa				
Ambient Temperature	-25°C ~ 60°C [-4°F ~ 140°F]				
Relative Humidity	< 95% (no condensation)				
Ex-Proof Mark	Exd II CT6 Gb/ Ex tD A21 IP68 T80°C				
MECHANICAL					
Housing	Stainless Steel 316L (also available in 304)				
Sunshade	Optional				
IP	IP68				
Cable Thread Hole	1pcs G3/4 or NPT3/4				
ELECTRICAL					
Voltage	AC24V (or AC85V~AC265V)				
Power	25W/35W (with thermostat)				
Surge Protection	Optional TVS6000V surge protect				
AMBIENT					
Ambient Temperature	-25°C to 60°C [-13°F to 140°F]				
Air Pressure	80Kpa to 106Kpa				
Relative Humidity	<95% (no condensation)				
GENERAL					
Cable	Integrated cable				
Dimensions (LxWxH)	213 x 213 x 570(mm) [8.4" x 8.4" x 22.4" (in)]				
Weight	15kg [33.1lbs]				
Mounted	Wall, Pole				
CAMERA					
Sensor	1/2.8", progressive scan, 2.0megapixel, CMOS				
Lens	5.2~114.4mm, AF automatic focusing and motorized zoom lens				
Optical Zoom	22				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	5.2	80.7	32.3	16.1	8.1
	114.4	1775.2	710.1	355	177.5
Angle of View (H)	55.9°~3.5°				
Angle of View (V)	33.5°~1.6°				
Angle of View (O)	68.8°~4.2°				
Shutter	Auto/Manual; shutter time: 1/6 s ~ 1/100000 s				
Minimum Illumination	Color: 0.001 lux (F1.5, AGC ON); B/W: 0.0001 lux(F1.5, AGC ON)				
Iris	Auto/Manual; F1.5 ~ F3.0				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital Noise Reduction	2D/3D DNR				
Defog	Digital Defog				
S/N	> 52dB				
WDR	120dB				

2MEP16-IP4M22X

4MP IP PTZ Dome Starlight Camera 22x with
Stainless Steel Explosion proof Housing – 316L Stainless Steel

VIDEO	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 Code Profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream: 4MP (2592×1520): Max. 20 fps; Sub Stream: 4MP (2560×1440): Max. 25 fps Third Stream: 1080P (1920×1080): Max. 30 fps
HLC	Supported
BLC	Supported
OSD	Up to 8 OSDs
ROI	Up to 8 areas
Privacy Mask	Up to 24 areas
Motion Detection	Up to 4 areas
SMART	
Behavior Detection	Intrusion, cross line, motion detection
Intrusion	Enter and loiter in a pre-defined virtual region
Cross Line	Cross a pre-defined virtual line
Motion Detection	Moving within a pre-defined virtual region
Recognition	Face detection, Audio detection
Intelligent Identification	Defocus, Scene Change
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP, Authentication, User Authentication
AUDIO	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
STORAGE	
Edge Storage	Micro SD, up to 128 GB
Network Storage	Supported
NETWORK	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API
PAN & TILT	
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 400°/s
	Preset speed: 540°/s
Tilt Range	-18° ~ +90° (auto reverse)
Tilt Speed	0.1° ~ 240°/s
	Preset speed: 400°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported

INTERFACE	
Audio I/O	Audio cable
	1 Input: impedance 35 kΩ; amplitude 2 V [p-p]
	1 Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	2/ 1
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
GENERAL	
Power	24 V AC±25%, 24 V DC±25%, PoE (IEEE802.3 at)
Power Consumption	8~ 20W

ATEX Markings Breakdown

