



## Features

- Support Ultra 265/H.265/H.264 video formats
- 8-channel input
- Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
- Support 1-ch HDMI, 1-ch VGA, HDMI at up 4K(3840x2160) resolution
- HDMI and VGA simultaneous output
- Up to 8MP resolution recording
- 1 SATA HDD up to 6 TB
- Support cloud upgrade

## Specifications

VIDEO/AUDIO INPUT	
<b>IP Video Input</b>	8-ch
<b>Two-way Audio Input</b>	1-ch, RCA
NETWORK	
<b>Incoming Bandwidth</b>	80Mbps
<b>Outgoing Bandwidth</b>	64Mbps
<b>Remote Users</b>	128
<b>Protocols</b>	P2P, UPnP, NTP, DHCP, PPPoE
VIDEO	
<b>HDMI/VGA Output</b>	HDMI: 3840x2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
<b>Recording Resolution</b>	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
<b>Audio Output</b>	1-ch, RCA
<b>Synchronous Playback</b>	8-ch
<b>Corridor Mode Screen</b>	3/4/5/7/9
DECODING	
<b>Decoding format</b>	Ultra 265/H.265/H.264
<b>Liveview/Playback</b>	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
<b>Capability</b>	2 x 4k@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30
HARD DISK	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	up to 6TB for each disk
EXTERNAL INTERFACE	
<b>Network Interface</b>	1 RJ45 10M/100M self-adaptive Ethernet Interface
<b>USB Interface</b>	Rear panel: 1 x USB2.0, 1 x USB3.0
POE	
<b>Interface</b>	8 independent 100 Mbps PoE network interfaces
<b>Max Power</b>	Max 30W for single port Max 108W in total (13.5W for each)
<b>Supported Standard</b>	IEEE 802.3at, IEEE 802.3af

# 2MN-8008P8-GS

8ch Network Video Recorder w/1 SATA Capacity and 8 POE

## GENERAL

<b>Power Supply</b>	52V DC Power Consumption: ≤8 W (without HDD)
<b>Working Environment</b>	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
<b>Dimensions (W×D×H)</b>	260 x 240 x 47 (mm) / 10.2"×9.4"×1.9" (in)
<b>Weight (without HDD)</b>	1kg (2.20 lb)

## Dimensions

