



## Features

- 24×10/100Mbps Ethernet ports
- 2×Gigabit combo ports (RJ45 and SFP)
- All 100Mbps ports support PoE
- PoE complies with IEEE802.3af/at, up to 30W for single port
- Up to 250m transmission distance on EXTEND mode
- Easy to use, no need to configure
- High quality with all metal housing

## Specifications

<b>Ports</b>	24×10/100Base-TX autosensing Ethernet ports (all support PoE) 2×Gigabit combo ports (RJ45 and SFP)
<b>Port Attribute</b>	10/100/1000Mbit/s transfer rate Half-duplex, full-duplex and auto-negotiation Auto MDI/MDIX
<b>Standards</b>	IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-X ANSI/IEEE 802.3 NWay IEEE 802.3x flow control IEEE 802.3af and IEEE 802.3at PoE
<b>MAC</b>	4K
<b>Packet Forwarding Rate</b>	6.55Mpps
<b>Switching Capacity</b>	8.8Gbps
<b>EXTEND Mode</b>	Disabled: all ports can communicate with each other, and monitoring optimization is disabled. Enabled: downlink ports can only communicate with uplink ports; monitoring optimization is enabled, and transmission distance can be extended to up to 250 meters.
<b>Status LEDs</b>	Link/Act (steady green): link is normal Link/Act (flashing green): data is being forwarded Link/Act (off): no link  PoE (steady orange): the port is powering a powered device properly PoE (off): the port is not connected to any powered device or is not supplying power  Power (steady green): AC input is normal Power (off): AC input is abnormal
<b>PoE</b>	802.3at/af, Max PoE capacity: 400 W
<b>Consumption</b>	≤ 450 W
<b>AC Voltage</b>	100-240 V
<b>Operating Temperature</b>	0°C-40°C (32°F-104°F)
<b>Operating Humidity</b>	10%-85%
<b>Storage Temperature</b>	-10°C-70°C (14°F-158°F)
<b>Storage Humidity</b>	10%-90%
<b>Dimensions (WxDxH)</b>	440mm×280mm×44mm (17.3"×11"×1.7")