



Line Frequency	31.5 - 60KHz
Field Frequency	56-75Hz, Flick-free
View Degree	Horizontal 176°
Connector Port	VGA or BNC, S-VHS, RGB, CVBS
GENERAL	
Cable	Integrated Cable
Size	441 x 200 x 348mm / 17.3" x 7.8" x 13.7" (in)
Weight	28kg / 61lbs
Mounted	Desk

Features

CERTIFICATION	
Certificate Mark	ExdIIB T6 Gb / Ex tD A21 IP68 T80°C
Certificate No	CNEx19.0326
Standards	Q/320412ZAF014-2018
MECHANICAL	
Housing	Carbon steel, Stainless steel 304 or 316L
IP	IP68
Cable Thread Hole	4 pcs G3/4 or NPT3/4 or M25 x 1.5
ELECTRICAL	
Voltage	AC100-240V
Power	50W
Surge Protect	Optional, TVS6000V surge protect
AMBIENT	
Ambient temperature	-25 to +60°C / -13 to 140°F
Air pressure	80Kpa to 106Kpa
Relative Humidity	95% (no condensation)
FUNCTION	
Screen	TFT-LCD, 15" inch
Resolution	1024 x 768
Brightness	220 nits
Contrast	700:1
Response Time	8/4 (Tr/Td) ms

Dimensions

