

2MEPIR16-IP4M22X

4MP IP Explosion proof PTZ Camera 22x Zoom – 316L Stainless Steel



Features

- 316L Stainless steel
- Certificate Mark: ExdII C T6 GB/DIP A20 TA, T6
- Protection enclosure: IP68
- 100m light distance
- Integrated cable
- Integrated with pan tilt station
- Infrared lights
- Wiper included
- Optical zoom 22x, digital zoom 16x

CERTIFICATES					
Certification		ExdII C T6 GB/DIP A20 TA, T6			
MECHANICAL					
Housing		Stainless Steel 316L (also available in 304)			
Wiper		Yes			
IP		IP68			
Cable Thread Hole		1pcs G3/4 or NPT3/4			
ELECTRICAL					
Voltage		AC85V~AC265V or DC24V or AC24V			
Power		50W/70W (with thermostat)			
AMBIENT					
Ambient Temperature		-25°C to 60°C [-13°F to 140°F]			
Air Pressure		80Kpa to 106Kpa			
Relative Humidity		<95% (no condensation)			
LIGHTS					
Light Distance		100m			
Light Control		Supports			
CAMERA					
Sensor		1/2.8", progressive scan, 4 megapixel, CMOS			
Lens		4.5~ 148.5mm, AF automatic focusing and motorized zoom lens			
Digital Zoom		16x			
Optical Zoom		22x			
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.5	69.8	27.9	14	7
	148.5	2094.8	837.9	419	209.5
Angle of View (H)		62.67°~2.82°			
Angle of View (V)		38.4°~1.3°			
Angle of View (O)		77.1°~3.3°			
Shutter		Auto/Manual; shutter time: 1s ~ 1/100000 s			
Minimum Illumination		Color: 0.001 lux (F1.5, AGC ON); B/W: 0.0001 lux(F1.5, AGC ON)			
Iris		Auto/Manual; F1.5 ~ F4.0			
Day/Night		IR-cut filter with auto switch (ICR)			
Digital Noise Reduction		2D/3D DNR			
Defog		Digital Defog			
S/N		>52dB			
WDR		120dB			
VIDEO					
Video Compression		Ultra 265,H.265, H.264, MJPEG			
H.264 Code Profile		Baseline profile, Main Profile, High Profile			
Frame Rate		Main Stream: 4MP (2592 x 1520): Max. 20 fps, 4MP (2560 x 1440): Max. 25 fps, 3MP (2048 x 1520): Max. 30fps; Sub Stream: 2MP (1920 x 1080): Max. 30 fps; Third Stream: D1(720 x 576): Max. 30fps			


2MEPIR16-IP4M22X

4MP IP Explosion proof PTZ Camera 22x Zoom – 316L Stainless Steel

HLC	Supported
BLC	Supported
EIS	Supported
OSD	Up to 8 OSDs
ROI	Up to 8 areas
Privacy Mask	Up to 24 areas
Motion Detection	Up to 4 areas
SMART	
Behavior Detection	Intrusion, cross line, motion detection, auto tracking
Intrusion	Enter and loiter in a pre-defined virtual region
Cross Line	Cross a pre-defined virtual line
Motion Detection	Moving within a pre-defined virtual region
Auto Tracking	Tracking the specified target
Recognition	Face detection, Audio detection
Intelligent Identification	Defocus, Scene Change
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP, Authentication, User Authentication
AUDIO	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
STORAGE	
Edge Storage	Micro SD, up to 128 GB
Network Storage	Supported
NETWORK	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x., SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API
PAN & TILT	
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 400°/s Preset speed: 400°/s
Tilt Range	1° ~ +90°
Tilt Speed	0.1° ~ 240°/s Preset speed: 240°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported
INTERFACE	
Audio I/O	Audio cable 1 Input: impedance 35 kΩ; amplitude 2 V [p-p] 1 Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	2/1

Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
GENERAL	
Power	24 V AC±25%, 24 V DC±25%, PoE (IEEE802.3 at)
Power Consumption	MAX 16W
Reset Button	Supported

Dimensions



ATEX Markings Breakdown

