

# 2MWT-i18Z

## Indoor Rated, 18 Zone Walkthrough Metal Detector with LED Bars



### Certifications

- ISO9001, ISO14001, HSMS18001, CE
- Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center
- In accordance with: EN60950, WN50081-1, EN50082-1
- Electric safety: EN60950
- Anti-interference standard: EN50082-1

#### Features

- Indoor 18 zones
- Extremely high sensitivity to find even the smallest of threats
- · Operation: Keyboard and remote control
- · User friendly interface operation for LCD
- Four LED light bars on both door panels: gives alarm corresponding to the height or human body.
- 18 zones identify multiple target locations from head to toe
- Sensitivity adjustable from Level 0 to 300 High: Can detect a clip; Low: Detects big metal articles such as knives, guns, copper, aluminums, zinc (more than 150g), bypasses metal in belt, buttons and shoes.
- Shock proof to avoid false alarms.
- · Sound and light alarm.
- Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.
- Tamper-Proof: operating system is password protected.

- Adjustable operating frequencies: Helps eliminate the potential interference from X-ray units, radios and other electrical items.
- Mix distance between two walkthoroughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
- · Harmless to pregnant women and patients with pacemakers
- · ADA Compliant
- · WIFI Network Capability option available
- Connect with computer, camera, turnstile, etc... (optional)

#### Specifications

Zone Options	18 zones options
Operation	Keyboard and remote control
LED Lights	4
Display	LCD
Pinpoint Zones	6 to identify multiple target locations head to toe
Tracking	Traffic and alarm counters that calculate traffic flow and resultant alarms
Alarm	Audible and Light Alerts
Adjustable Sensitivity	From Level 0 to 300 High
Tamper Proof	Yes
Operating Frequencies	Adjustable
Distance	Mix distance between two walkthoroughs from 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
Safety	Harmless to pregnant women and pacemakers
Electrical Current	AC215V~230V; 50/60Hz
Power	35W
Work Environment	-20°C~+45°C
Gross Weight	209.4 lbs
Outer Frame	2220mm (h) x 820mm (w) X 522mm (d) 87.4" x 32.3" x 20.6" (HxWxD) (inches)
Inner Frame	2000mm (h) X 700mm (w) X 522mm (d) 78.7" x 27.6" x 20.6" (HxWxD) (inches)