

2MWT-i24Z

Indoor Rated, 24 Zone Walkthrough with Intelligent DSP



Certifications

- ISO9001, ISO14001, HSMS18001, CE
- Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center
- In accordance with: EN60950, WN50081-1, EN50082-1
- Electric safety: EN60950
- Anti-interference standard: EN50082-1

Features

- Stable performance in 24 zones
- DSP technology, automatic calibration
- . Two LED lights, LCD display
- Self-diagnostic capability
- Input MBSU battery backup, in time power transfer
- · Modular structure for easy maintenance
- · Intuitively adapts to a working environment
- · Auto scans for environmental interference
- · Easy to operate LCD interface
- Two LED light bars on both door panels: Gives alarm corresponding to the height or human body
- Detection Zones can be adjusted from 1 zone to 8,16 or 24 zones
- Adjustable Sensitivity: From Level 0 to 300 High: Can detect up to a paper clip.
 Low: Detects big metal articles such as: knives, guns, copper, aluminums, zinc (more than 150g), bypassing metal in belts, buttons and shoes
- Shock proof to avoid false alarms

- · Sound and light alarm
- Intelligent traffic and alarm counters to calculate traffic flow & resultant alarms
- Tamper-Proof: Operating system is password protected
- Adjustable operating frequencies: Helps eliminate the potential interference from X-ray units, radios and other electrical items
- Mix distances between two walkthroughs: 0.3 meters at low sensitivity,
 0.5 meters at high sensitivity
- · ADA compliant models available
- · WIFI network capability option available
- · Harmless to pregnant women and heart pacemakers
- Connect with computer, camera, turnstile, etc... (optional)

Specifications

Zone Options	8-16-24 zones options
Shock Proof	Yes
LED Bars	2
Display	LCD
Calibration	Automatic
Tracking	Traffic and alarm counters that calculate traffic flow and resultant alarms
Alarm	Audible and Visual Alerts
Adjustable Sensitivity	From Level 0 to 300
Tamper Proof	Password Protected
Operating Frequencies	Adjustable
Distance	Mix distances between two walkthroughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity.
Safety	Harmless to pregnant women and pacemakers
Electrical Current	AC215V~230V; 50/60Hz
Power	15W
Work Environment	-20°C~+55°C
Gross Weight	209.4 lbs
Outer Frame (HxWxD)	2210(h) x 880(w) x 600(d) (mm) 87.4" x 32.3" x 20.6" (in)
Inner Frame (HxWxD)	2010(h) x 760(w) x 600(d) (mm) 78.7" x 27.6" x 20.6"