



Certifications

- ISO9001; ISO14001; HSMS18001; CE
- Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center
- In accordance with: EN60950, WN50081-1, EN50082-1
- Electric safety: EN60950
- Anti-interference standard: EN50082-1

Features

- Indoor 18 zones
- IP55 weather rated for outdoor use
- Extremely high sensitivity to find even the smallest of threats
- Operation: Keyboard and remote control
- User friendly interface operation for LCD
- Four LED light bars on both door panels: gives alarm corresponding to the height or human body.
- 18 zones identify multiple target locations from head to toe
- Sensitivity adjustable from Level 0 to 300 High: Can detect a clip; Low: Detects big metal articles such as knives, guns, copper, aluminums, zinc (more than 150g), bypasses metal in belt, buttons and shoes.
- Shock proof to avoid false alarms.
- Sound and light alarm.
- Intelligent traffic and alarm counters that calculate traffic flow and resultant

alarms.

- Tamper-Proof: operating system is password protected.
- Adjustable operating frequencies: Helps eliminate the potential interference from X-ray units, radios and other electrical items.
- Mix distance between two walkthoroughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
- Harmless to pregnant women and patients with pacemakers
- ADA Compliant
- WIFI Network Capability option available
- Connect with computer, camera, turnstile, etc... (optional)

Specifications

Zone Options	18 zones
Shock proof	Yes
LED Lights	4
Display	LCD
Pinpoint Zones	Pinpoint zones to precisely identify multiple target locations from head to toe, can update 12 & 18 zones
Tracking	Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms
Advanced Broadband Detection	Can detect ferrous and non-ferrous articles.
Alarm	Audible and Visual Alerts
Adjustable Sensitivity	From Level 0 to 99
Tamper Proof	Password Protected
Operating Frequencies	Adjustable
Distance	Mix distance between two Walk-throughs: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity.
Safety	Harmless to pregnant women and heart pacemakers
Electrical Current	AC215V~230V; 50/60Hz
Power	35W
IP Rating	IP55
Work Environment	-20°C ~ +45°C
Gross Weight	209.4 lbs
Outer Frame	2220mm (h) x 820mm (w) X 522mm (d) 87.4" x 32.3" x 20.6" (HxWxD) (inches)
Inner Frame	2000mm (h) X 700mm (w) X 522mm (d) 78.7" x 27.6" x 20.6" (HxWxD) (inches)