



Features

- Single axle
- 3 Bullet cameras and 1 dome camera
- Mast height 9m/29' ft 6" in
- Wind rating speed 100kph
- Manual mast raise/extension
- Transition AC to DC 12V
- 50mm ball with 4412 lbs capacity

Specifications

PERFORMANCE	
Powered	AC Input
Connector	AC Input Socket
Transition	AC to DC 12V
Wind Rating Speed	100 km/h
Protection Level	IP65
DIMENSIONS AND WEIGHT	
Size (not including mast)	2930 x 1320 x 1500 (mm) / 4'4" x 9'7" x 10" 5" (ft and inches)
Weight	520Kgs / 1146 lbs
20 ft. Container Can Fit	5 sets
CAMERA AND MAST	
Dome PTZ Camera	1 x 2M Technology PTZ Camera
PTZ Camera Specs	2MP HD, 20x Optical Zoom, IR150m, 360° View
Bullet Camera	3 x 4M Technology Bullet Cameras
Bullet Camera Specs	4MP, HD IR50m
Mast Height	9 meters / 29' ft 6" in.
TRAILER	
Axle	Single
Tire	YOK 205/70 R15
Mast Raise/Extension	Manual
Mast Rotation	Optional
Drawbar	A-type drawbar with grating plate
Brake System	Bump brake (pintle ring hitch/50mm ball hitch) & brake disc assembly & wheel chock
Tow Hitch	50 mm Ball 4412 lbs
Shock Absorber	Double eye leaf spring
Tail Lamp	ADR Standard
Outrigger	7000 LBS jack and high strength square tube / manual
Fire Extinguisher	SAI/EN3/CE Certification
ELECTRICAL PARTS	
Loudspeaker	Optional
Breaker, Relay, Switch, PV Cable and Connector, etc.	All electrical parts have UL Certification
GPS	Optional
OTHER	
Packing	Plywood Case/Wooden Case/EPE Foam
Warranty	Camera: 1 year or 2500 hours, whichever comes first Trailer: 3 years or 7500 hours, whichever comes first