



### Optional Features

- 24V/120V Inverter for AC power support
- 16A battery charger for faster recharging
- Spare wheel for quick replacement and minimal downtime
- Anti-theft measures
- Alternate solar panel configurations
- PTZ camera for wide-area coverage
- Bullet camera for long-range monitoring
- Expanded battery capacity for extended runtime
- Taller mast height for improved visibility
- Manual, electric, or hydraulic mast options
- Various tow hitch types for different vehicles

### Specifications

<b>System</b>	DC 24V
<b>Solar Panel</b>	2x 410W, Changeable Angle
<b>Battery</b>	4x 150A Gel
<b>Battery Pack Usable Capacity</b>	5.76 kwh
<b>Spiral Cable</b>	CAT6*2+18 Gauge*4
<b>MPPT</b>	150/35 VE.Can
<b>ATM Weight</b>	2050 lb
<b>Trailer Length</b>	132.7"
<b>Trailer Width</b>	70"
<b>Trailer Height</b>	98.5"

### Features

- Rugged solar security trailer with 2 adjustable solar panels
- High-capacity gel battery system for extended off-grid operation
- Foldable drawbar for compact transport and storage
- Manual 18ft telescoping mast with 60mph wind rating
- 5 manual stabilizer supports for secure positioning
- Galvanised steel subframe for superior corrosion resistance
- Powder-coated guards for added durability and protection
- Single axle with Australia/Europe/North America standard
- US DOT-approved lighting package for road compliance



<b>Trailer Type</b>	Single Axle
<b>Tire and Rim Size</b>	13"
<b>Mast Raise/Extension</b>	Manual
<b>Mast Height</b>	18 ft
<b>Wind Rating Speed</b>	60 mph
<b>Stabilizer Supports</b>	5x Manual
<b>Drawbar</b>	Foldable
<b>Lighting Package</b>	US DOT-approved
<b>Mud Guard/Wheel Chock</b>	Special Design
<b>Working Temperature</b>	-35°C to +60°C (-31°F to +140°F)

## Diagrams

