



Features

- 38mm/1.49" in self-leveling CCD camera head
- Frame 40/50/60 - 131'/164'/196' ft
- Fiberglass cable 9mm @yellow fiber glass, meter counter & text and wheel
- Tool Box, 7" DVR & Lithium ion battery inside
- Wireless Keyboard
- U type handle
- Spiral cable with 6x pin aviation plug

OTHER SIZES AVAILABLE

2MPIC-40131	131.23 Feet / 40m fiberglass cable
2MPIC-40164	164.04 feet / 50m fiberglass cable
2MPIC-40197	196.85 feet/ 60m fiberglass cable
2MPIC-40394	393.70 feet /120 m fiberglass cable

OPTIONAL

512Hz sonde into camera head

Wireless Keyboard

Items Included

- Tool bag
- 72mm/2.83" in Roller Skid
- 120mm/4.72" in universal Skid
- DVR remote
- 12V 1.5A power adapter
- 12V 2A car charger
- Screwdriver, hexagon spanner, inner hexagon spanner
- User manual



Specifications

CAMERA	
Camera Size	Ø 38 x 81 (mm) / Ø 1.49" x 3.18" (in.)
Camera Total Length	318mm / 12.5" in
Sensor	1/3" Sony CCD, 700 TVL
Pixel	976 (H) x 582 (V)
View Angle	120°
Self Leveling	Built-in
Focus Distance	12cm / 4.7" in
Depth-of-Field	120cm / 40.2" in
Front Lens	Sapphire glass
Waterproof	20m/65.6' ft. Under Water (Camera fixed on Cable)
Shell Material	#304 stainless steel
Lighting	Built-in 4x LED (White)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (4°F ~ 140°F)
MONITOR	
Screen	7-inch 16:9 Super bright HD color LCD screen
Resolution	800 x 480 RGB
Mirror and Flip	Supports image mirror, and flip
Video Resolution	720 x 576 25fps Max
Video Encoding	H.264
Photograph	720 x 480 / 720 x 576
Audio Recording	Local sound record
Output	TV and audio output
External Memory	SD memory card up to 32GB
Data Output	USB 2.0 to PC
LED Driver	Built-in dimmer
On Screen	Date, time, Distance (m/ft) display
Battery Capacity	7.4 V 4400mAh lithium ion battery
Power Supply	DC 12V input
Life/Charge Time	5/8 hours
Language	English, German, French, Spanish, Italian, Chinese, Japanese, Russian, Portuguese
CABLE WHEEL	
Push Rod	60-120M fiberglass push rod cable with on-screen distance counter
Push Cable Diameter	9mm
OPTIONAL	
Camera head with built-in 512Hz sonde	
Camera Skids	Caster Skid: POM Ø 134 x 83.9 30mm Wheel
	POM Skid: POM Ø 78 x 83.9
	Ball Support: POM S Ø 60 x 53.5
	Lock Sleeve: POM Ø 54.6 x 38
Cable Length Options	60m, 80m, 100m, 120m