



Features

- 38mm / 1.49" in self-leveling CCD camera head
- 40/50/60 - 131/164/196' ft
- Fiberglass cable 9mm @yellow fiber glass, meter counter & text and wheel
- Tool Box, 7" DVR & lithium ion battery inside
- Wireless keyboard
- U type handle
- Spiral cable with 6x pin aviation plug

OTHER SIZES AVAILABLE

9MM YELLOW FIBERGLASS CABLE

2MPICC-40262	262.47ft/ 80 meters fiberglass cable
2MPICC-40328	328.1 ft/ 100 meters fiberglass cable
2MPICC-40394	393.70 feet /120 m fiberglass cable

OPTIONAL

512Hz sonde into camera head

Items Included

- Tool bag
- 72mm / 2.83" in roller skid
- 120mm / 4.72" In universal skid
- DVR remote
- 12V 1.5A power adapter
- 12V 2A car charger
- Screwdriver, hexagon spanner, inner hexagon spanner
- User manual



Specifications

CAMERA	
Camera Size	38 x 81 (mm) / 1.49" x 3.18" (in.)
Camera Total Length	318mm / 12.5" in.
Sensor	1/3" Sony CCD, 700 TVL
Pixel	976 (H) x 582 (V)
View Angle	120°
Self leveling	Built-in
Focus Distance	12cm / 4.7" in. (approx.)
Depth-of-Field	120cm / 40.2" in. (approx.)
Front Lens	Sapphire glass
Waterproof	20m/65.6' ft. Under Water (Camera fixed on cable)
Shell Material	#304 stainless steel
Lighting	Built-in 12x LED (White)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (4°F ~ 140°F)
MONITOR	
Screen	7" in. 16:9 Super bright HD color LCD screen
Resolution	800 x 480 RGB
Mirror and Flip	Supports image mirror, and flip
Video Resolution	720 x 576 25fps Max.
Video Encoding	H.264
Photograph	720 x 480 / 720 x 576
Audio Recording	Local sound record
Output	TV and audio output
External Memory	SD memory card up to 32GB
Data Output	USB 2.0 to PC
LED Driver	Built-in dimmer
Playback	Video, Photo and Audio
On Screen	Date, time, Distance (m/ft) display
Battery Capacity	7.4 V 4400mAh lithium ion battery
Power Supply	DC 12V input
Life/Charge Time	5/8 hours
Language	English, German, French, Spanish, Italian, Chinese, Japanese, Russian, Portuguese
OPTIONAL	
Camera Head Add On	Built-in 512Hz sonde
Camera Skids	Caster Skid: POM Ø 134 x 83.9 30mm Wheel
	POM Skid: POM Ø 78 x 83.9
	Ball Support: POM S Ø 60 x 53.5
	Lock Sleeve: POM Ø 54.6 x 38