



Specifications

CAMERA	
Pipe Diameter	200-2000mm
Weight	about 3kg (with no battery)
CCD Type	1/3 inch COMS
Resolution	1280 x 960
Zoom	20x optical zoom
Tilt	Motorized – Up: 45°, down: 45°
Illumination	0.05 Lux @ F1.6
Combined Brightness	Main light: 10W x 2 LED; neutral white/warm white; CCT 5000K Auxiliary light: 3W x 2 LED; neutral white/warm white; CCT 3700K
Precision Range	0.05m-70m
Laser Range Mode	Phase type
Wireless Transmission Mode	802.11A/N + 2.4G
Operating Temperature	-10°C to 60°C
Ingress Protection	IP68
Anti-crash Telescoping U-shaped probe	Adjustable Height (range: 70cm to 120cm)
Battery Capacity	2600MA, works continuously for 2.5 hours
TABLET	
Screen Size	10" inches, touch screen
RAM	4GB
ROM	64GB, supports SD (TF card), extend storage 256GB
Battery Capacity	7000mAh
TELESCOPE	
Retracted Length	1.58cm
Number of Knobs	6
Weight	2.5 kg
WIRELESS REPEATER	
Device Hub	Wireless, provides
Output	DC5V 1A
POWER	
Charge Connector	3x 16.8V 1A
USB	2x 5V 2.1A
Dimensions	203 x 145 x 76 (mm)
Material	Aluminum

Overview

The 2MMHCPZ HD wireless manhole camera which includes the 10" inch tablet controller with a capacity of 64GB for storage. Using an additional memory card storage can be increased up to 256GB.

Features

- 20x optical zoom camera with motorized tilt motion
- 2x high brightness LEDs for long distances and 2x for close distance viewing
- 10" touch screen display controller
- 7m/23' ft. telescopic rod
- 32GB memory card
- U style probe
- Built-in laser for distance counter
- Battery is included

OTHER SIZES AVAILABLE

2MMHCPZ-23	7m/23' ft. telescopic pole
2MMHCPZ-39	12m/39.4' ft. telescopic pole
2MMHCPZ-49	15m/49.2' ft. telescopic pole

Components



Wireless Manhole Camera




Touch Screen Tablet



Telescope



Repeater



Connection Panel