

X-Ray Baggage Scanner

2MX-4233

Product highlights

- * Power on self test (POST)
- * Multilingual operation
- * Secure access Key
- * Threat alert and material classification
- * Auto archiving
- * Energy saving design
- * One key turn off
- * Drugs and explosives inspection



Physical Specifications

Unit weight (kgs)	202
Unit size (mm)	1531(L)*668(W)*860(H)
after packed in wooden pallet -	
Gross weight (kgs)	265
Packing size	165*85*107cm

General Specifications

Tunnel size(mm)	420(L)*330(W)
Conveyor Speed(m/s)	0.22
Conveyor height(mm)	273
Conveyor Max Load(kgs)	50
X ray dose per each inspection	$\leq 2 \mu\text{Gy}$
X ray leakage	$< 1 \mu\text{Gy/h}$ at any point 5 centimeters outside the external surface
Steel penetration	8 mm guaranteed
Wire Resolution	Dia 0.0787mm copper wire (AWG40) guaranteed

Penetration Resolution	Dia 0.202mm copper wire (AWG32) guaranteed
Spatial resolution:	Horizontal:dia 1.3mm, Vertical: dia 1.0mm
Power Consumption	max. 400W
Noise	<60 dB
Film Safety	Guarantee ASA/ISO1600 Film

X-ray Generator (single)

Anode Voltage	80 KV
Ray direction	Downward
Cooling / Duty Cycle	Sealed oil cooling /100%

Imaging System

X-ray Sensor	L-Shaped Photodiode Array, 12bit deep
Images process	24bit real time processing ,4colors analysis, Images displayed marked date and ID No., Count the number of bags
Image display	High resolution of 1920*1080 pixel; Image Grey Level: 4096
Image Enhancement	1-32 times enlargement continuity, Color/BW, negative, high/low penetration enhancement, brightening, darkening, gray level scan, super enhancement, elimination of organics/inorganics, local enhancement, pseudo color processing, edge enhancement, etc.
Explosives & Narcotics Detection	Suspicious organics highlight(atomic number Zeff=7,8,9)
Suspicious Alarm	Alarm and box line the suspicious objects including hard to penetrate material, explosives and drugs
Threat Image Projection(TIP)	Inserting fictional, but realistic images of threat items into baggage during screening operation, for maintenance of vigilance, as well as training and assessment of image identification capability
Image Recall	30 images recallable
Image Archive	Up to 10,000 images stored automatically, enable transferring to USB disk, and converting to JPG format
Miscellaneous Functions	Time/date display, counters, user management, system-on/X-ray-on timers, power on self test, built-in diagnostic facilities, system log, system standby and stimulant training, etc.
Options	Dual-direction scanning, intelligent roller, etc.

Operating Environment

Operation temperature/Humidity	5℃-40℃ / 0%-90%(non-condensing)
Storage Temperature/Humidity	-20℃to 60℃ / 10%-90%(non-condensing)
Operation Power	220VAC(±10%) 50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)
UPS	Options: 5mins, 30mins, etc

Computer and other

Monitor	One 17-inch LCD monitor, 1280*1024, no console desk
RAM	1GB
Keyboard	Special designed
System	Embedded Linux operating system, multi core ARM, stable and reliable

Compliance

International	<ul style="list-style-type: none">* ISO19001 ; ISO14001 ; ISO45001 ;* CE RoHS* FDA FCC
---------------	--

