

# Heater Control Vandal-Proof Dome Housing

6-inch, IK10 vandal resistant, die-cast aluminum construction



## Features

- 6-inch polycarbonate dome bubble
- Designed for indoor and outdoor applications
- Die-cast aluminum construction
- IP66, NEMA-4X enclosure rating
- IK10 (20J) vandal resistant
- Dual wall construction strengthens the heat insulation
- Built-in heater and blower (optional)
- Included safety wire
- Resistant to 1,000 hours of salt fog testing (according to ISO9227)
- Internal adjustable support for camera
- Clear or smoked dome bubble (available)

## Specifications

- **Type:** 6-inch, indoor/outdoor, dome housing
- **Protection Rating:**
  - IP66, NEMA-4X enclosure rating
  - IK10 (20J) vandal resistant
- **Material:** Die-cast aluminum, polycarbonate dome bubble
- **Finish:** Beige polyester powder coat
- **Input Power:** 12 V DC
- **Power Consumption:** 12 W maximum
- **Dimensions (Ø × H):** 220 mm × 336 mm (8.7 in × 13.2 in)
- **Internal Usable Size (Ø):** 153 mm (6 in)
- **Heater Control:** On at 5 °C ± 3 °C (41 °F ± 5 °F), off at 15 °C ± 3 °C (59 °F ± 5 °F) (optional)
- **Blower Control:** On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) (optional)
- **Operating Ambient Temperature:** -40 °C to 50 °C (-40 °F to 122 °F)
- **Bubble:** 2 mm (0.08 in), clear or smoked (available)
- **Certifications:** CE, FCC, RoHS, IP66, IK10