



Specifications

GENERAL SPECIFICATIONS	
Window Viewing Area (Ø)	73 mm (2.9 in)
Atmospheric Pressure	86 kPa to 106 kPa
Operating Humidity	5 % to 95 % non-condensing
Operating Temperature	-40 °C to 60 °C (-49 °F to 140 °F)
Protection Level	- Ex d IIC T6 Gb explosion-proof marking - IP68, NEMA-6P enclosure rating
Dimensions (L x W x H)	160 mm × 160 mm × 405 mm (6.3 in × 6.3 in × 15.9 in) 160 mm × 200 mm × 405 mm (6.3 in × 7.9 in × 15.9 in)
Internal Usable Dimensions	105 mm × 330 mm (4.1 in × 13.0 in)
Net Weight	8 kg (17.6 lb)
Material	Stainless steel 304/316L
Heater Control	On at 1 °C ± 3 °C (34 °F ± 5 °F) (optional)

Features

- IP68, NEMA-6P enclosure rating for protection against dust and water
- Operating temperature range: -40 °C to 60 °C (-49 °F to 140 °F)
- Explosion-proof marking: Ex d IIC T6 Gb
- Construction: AISI 304/316L stainless steel (optional)
- Accessories: Wiper and sunshield included (optional)