



### Specifications

GENERAL SPECIFICATIONS	
<b>Window Viewing Area (Ø)</b>	73 mm (2.9 in)
<b>Atmospheric Pressure</b>	86 kPa to 106 kPa
<b>Operating Humidity</b>	5 % to 95 % non-condensing
<b>Operating Temperature</b>	-40 °C to 60 °C (-49 °F to 140 °F)
<b>Protection Level</b>	<ul style="list-style-type: none"> <li>Ex d IIC T6 Gb explosion-proof marking</li> <li>IP68, NEMA-6P enclosure rating</li> </ul>
<b>Dimensions (L x W x H)</b>	<ul style="list-style-type: none"> <li>160 mm × 160 mm × 405 mm (6.3 in × 6.3 in × 15.9 in)</li> <li>160 mm × 200 mm × 405 mm (6.3 in × 7.9 in × 15.9 in)</li> </ul>
<b>Internal Usable Dimensions</b>	105 mm × 330 mm (4.1 in × 13.0 in)
<b>Net Weight</b>	8 kg (17.6 lb)
<b>Material</b>	Stainless steel 304/316L
<b>Heater Control</b>	On at 1 °C ± 3 °C (34 °F ± 5 °F) (optional)

### Features

- IP68, NEMA-6P enclosure rating for protection against dust and water
- Operating temperature range: -40 °C to 60 °C (-49 °F to 140 °F)
- Explosion-proof marking: Ex d IIC T6 Gb
- Construction: AISI 304/316L stainless steel (optional)
- Accessories: Wiper and sunshield included (optional)