



Features

- Available in 304 or 316L stainless steel construction
- Dome cover made from polycarbonate aviation-grade composite for high strength and superior corrosion resistance
- Supports dome and PTZ cameras

Specifications

GENERAL SPECIFICATIONS

Atmospheric Pressure	80 - 106 KPa
Operating Humidity	≤95 % RH (+25°C)
Operating Temperature	-30°C ~ +70°C (-22°F ~ 158 °F)
Certificate Mark	Ex d IIC T6 Gb/Ex tD A21 IP68 T80°C
Dimensions (Ø × H)	240 mm × 304 mm (9.45 in × 11.97 in)
Cable Thread Hole	M25
Ingress Protection	IP68
Weight	≤23 kg (50.71 lbs)
Material	Stainless steel 304/316L
Surface Treatment	Stainless Steel Original Color, electropolishing (optional)
Rotation Angle	Horizontal 0°-360°, vertical -90° - +90°
Rotation Speed	Horizontal 1-300°/s, vertical 1-180°/s
Method of Installation	Wall mounting, lifting installation

ELECTRICAL FEATURES

Power Supply	AC 24V
Working Current	≤ 2A
Cable Output	Integrated cable, 0.8 meters
Automatic Mode	Automatic cruise or any setting two rounds
Pre-Position	256 Locations (Selectable)

Dimensions

